LEDLENSER

























OUTDOOR & SPORTS HOME & LIFE PRODUCT CATALOG


POWERUP













2-3 CONTENT

4-9 NEW PRODUCTS

- 9 HF4R Core NEW
- 9 HF6R Core NEW
- 9 HF8R Core NEW

10-25 FLASHLIGHTS

- 12 P2R Core
- 12 P3 Core
- 13 **P4 Core**
- 13 P4R Core
- 14 P5 Core
- 14 P5R Core
- 15 **P6 Core**
- 15 P6R Core
- 19 **P7 Core**
- 19 **P7R Core**
- 19 **P17R Core**
- 20 P6R Core QC
- 24 P6R Signature
- 24 P7R Signature
- 25 P18R Signature

26-29 KEYRING LAMPS



- 28 **K4R**
- 29 **K6R**
- 29 K6R Safety

30-35 KIDSLIGHTS



- 33 KIDLED2
- 33 KIDLED4R
- 34 KIDBEAM4
- 34 KIDCAMP6



- **36-41 X-SERIES**
 - 39 **XP30R NEW**
 - 40 **X21R**





RETURN TO THE MENU QUICKLY FROM ANY PAGE

CONTENT CLICKABLE CONTENT


OUTDOOR & SPORTS HOME & LIFE

42-55 HEADLAMPS



- 46 **H5 Core**
- 46 H5R Core





47 **H19R** Core



- 51 H7R Signature
- 51 **H19R Signature**



- 54 **NEO1R**
- 55 **NEO3**
- 55 **NEO5R**
- 55 **NEO9R**

56-57 CLIPLIGHT




- 57 **CU2R**
- 58-63 LANTERNS
 - 62 **ML4**
 - 62 ML4 WL
 - 63 **ML6**
 - 63 ML6 WL
 - 63 ML6 WL Connect

64-69 PORTABLE ENERGY



- 66 FLEX5 66 FLEX10
- 68 FLEX3
- 68 FLEX7
- 70-73 ACCESSORIES
- **76-79 TECHNOLOGIES**
- **80-81 ABOUT US**
- 82-83 WARRANTY + ISO
- 84-85 NOTES + CONTACT

NOVELTIES
THE HF-SERIES



HF8RCORE & NEW

REVOLUTIONARY TECHNOLOGIES FOR MAXIMUM FLEXIBILITY:


With the HF8R, Ledlenser introduces its first hands-free headlamp. Why break your flow at work when your headlamp will adjust automatically or transition seamlessly, while providing you with the perfect light pattern. Without a battery box at the back of your head or an additional cable at the headband, you will be more comfortable and move more freely.














- 01-Powerful~headlamp~with~additional~red~front~light
- **02 Automatic dimming and focusing** thanks to our **Adaptive Light Beam Technology** the system detects reflections and lighting conditions and automatically controls all light sources separately. This allows the HF8R to be used completely hands-free.
- **03 Powerful battery** can easily be recharged via **Magnetic Charge System**
- **04** Water and dustproof (IP68)
- **05** Large scope of delivery for versatile options and use
- 06 Lamp head tilts steplessly
- **07** Perfect light pattern for any range and virtually seamless focusing thanks to our **Digital Advanced Focus System**; optional manual operation via **Focus Wheel**
- **08** High-quality **aluminum housing**
- **09** Remote control via **Ledlenser Connect App** (upgrade with additional features available)



















(USB-C)



HF6R CORE



, des	able	9
2	\equiv	
5/	ы	1
0	ш	de
-	ш	9

2x High Power LED, 1x Red LED	2x Xtreme LED, 1x High Power LED, 1x Red LED	3x Xtreme LED, 1x High Power LED, 1x Red LED
Boost / Power / Mid Power / Low Power (+ Red Light)	Boost / Power / Mid Power / Low Power (+ Red Light)	Boost / Power / Mid Power / Low Power (+ Red Light) (+S.O.S., Alpine distress signal via App)
500 / 300 / 120 / 20	800 / 500 / 250 / 20	1600 / 900 / 300 / 20
130 / 100 / 60 / 15	160 / 140 / 80 / 25	210 / 200 / 100 / 25
- / 2.5 / 5 / 35	-/3/6/60	- / 3.5 / 10 / 90
5200 – 6200	5200 – 6200	5200 – 6200
70	70	70
1x Li-ion Battery Pack 3.7V	1x Li-ion Battery Pack 3.7V	1x Li-ion Battery Pack 3.7V
3.7 / 1000	7.4 / 2000	13.7 / 3700
IP68	IP68	IP68
Yes	Yes	Yes
180	225	270
2	2	2
72 / 2.54	126 / 4.44	194 / 6.84
		•
	•	•
•	•	•
•	•	•
	•	•
Fusion Beam, Transportation Lock, Memory Function, Backup Mode, Battery Indicator, Charge Indicator, Low Battery Warning	Memory Function, Transportation Lock, Backup Mode, Aluminum housing, Battery Indicator, Charge Indicator, Low Battery Warning	Bluetooth®, Transportation Lock, Memory Function, Backup Mode, Aluminum housing, Emergency Light, Battery Indicator, Charge Indicator, Low Battery Warning
Black: 502790 / 4058205031684	Black: 502796 / 4058205031837	Black: 502801 / 4058205031943
Blue: 502791 / 4058205031707	Blue: 502966 / 4058205034319	
Red: 502792 / 4058205031738	Red: 502967 / 4058205034340	
	O White: 502797 / 4058205031851	

Connect Adapter, Magnetic Charging Cable Comfort Pad, Connect Adapter, Magnetic

Charging Cable (USB-C)

LED

 $\ \ \, \triangle \ \ \, \mathsf{LED} \, \mathsf{Configuration} \\$

□III Light Functions

-\(\hat{\tau}\)- Luminous Flux¹ (lm)

□→ Beam Distance¹ (m)

L Run Time¹ (h)

Color Temperature (K)

(R) Color Rendering Index (CRI)

BATTERY AND CASE

■ Battery

Battery Capacity² (Wh / mAh)

O IP Level

Rechargeable

harging Time⁵ (min)

Drop Height (m)

WEIGHT

Weight incl. Battery (g / oz)

TECHNOLOGIE

Adaptive Light Beam

Digital Advanced Focus System

Magnetic Charge System

Temperature Control System

Cooling Technology

More Features

PACKAGING

Item no. Box / GTIN

Item no. Box / GTIN

Item no. Box / GTIN

Content Box

Optional accessories on page 72

1-8 Information on page 84

Comfort Pad, Connect Adapter, Magnetic

Charging Cable (USB-C), removable

Overhead Strap

FLASHLIGHTS









—P-SERIES CORE





		I ZIN COINE	I J COILL
	ED		
$\overline{\triangle}$	LED Configuration	1x Power LED	1x Power LED
all	Light Functions	Power / Mid Power / Low Power	Power / Mid Power / Low Power
<u>-\̈́\</u> -	Luminous Flux¹ (lm)	120 / 50 / 15	90 / 50 / 15
	Beam Distance¹ (m)	65 / 45 / 15	110 / 70 / 40
<u>(b)</u>	Run Time ¹ (h)	0.5 / 1 / 5	3 / 4 / 6
Ĵκ	Color Temperature (K)	6000 - 7500	6000 - 7500
(CRI)	Color Rendering Index (CRI)	70	70
	BATTERY AND CASE		
<u> </u>	Battery	1x Li-ion Battery 3.7V mit Micro-USB	1x Micro (AAA) Alkaline 1.5V
III-)	Battery Capacity² (Wh / mAh)	0.74 / 200	
රු	IP Level	IP54	IP54
Φ	Rechargeable	Yes	No
Ð	Charging Time ⁵ (min)	150	
<u>*</u>	Drop Height (m)	2	2
S	SIZE AND WEIGHT		
7	Length – Defocused (mm)	103	96
\bigcirc	Head Diameter (mm)	15	20
<u>a</u>	Weight incl. Battery (g / oz)	36 / 1.3	42 / 1.5
Т	ECHNOLOGIE		
1	Smart Light Technology		
	Flex Sealing Technology		
00	Magnetic Charge System		
	Temperature Control		
	Advanced Focus System	•	•
	More Features	Energy Saving	Rapid Focus
P	PACKAGING		
	Item no. Box / GTIN	502176 / 4058205020367	502597 / 4058205028462
	Content Box	1 Battery Set, Pocket Clip, Micro-USB Charging Cable	1 Battery Set, Pocket Clip
C	PTIONAL ACCESSORIES		
		502248 Lamp Adapter Type A	0337 Pouch Type D
		0337 Pouch Type D	502248 Lamp Adapter Type A
F	urther accessories on page 70	0380 USB Car Charger	

A service I	eable
0	DAD CODE
P4 CORE	P4R CORE
TTOOKE	
1x Power LED	1x Power LED
Power / Mid Power / Low Power	Power / Mid Power / Low Power
120 / 60 / 15	200 / 90 / 15
90 / 55 / 25	90 / 60 / 15
5 / 9 / 20	1.5 / 3 / 25
6000 - 7500	6000 - 7500
70	70
2x Micro (AAA) Alkaline 1.5V	1x Li-ion Battery Pack 3.7V
	2.22 / 600
	IP54
No	Yes
	150
2	2
146	150
15	15
58 / 2.0	55 / 1.9
•	•
	Energy Saving
502598 / 4058205028493	502177 / 4058205020398
1 Battery Set, Pocket Clip	1 Battery Set, Pocket Clip, Micro-USB Charging Cable
502248 Lamp Adapter Type A	502248 Lamp Adapter Type A
	0380 USB Car Charger



¹⁻⁸ Information on page 84

— P-SERIES CORE







red<mark>dot</mark> winner 2021







reddot winner 2021





502248 Lamp Adapter Type B

502259 Charging Station Type A



		P5 CORE	P5R CORE
	ED		
\bigcap	LED Configuration	1x High Power LED	1x High Power LED
	Light Functions	Power / Mid Power / Low Power	Boost / Power / Mid Power / Low Power (+ Position, Blink, S.O.S., Strobe)
- <u>`</u> Ċ-	Luminous Flux¹ (lm)	150 / 60 / 15	500 / 350 / 130 / 15
□;	Beam Distance ¹ (m)	90 / 60 / 30	250 / 180 / 110 / 40
<u>(L)</u>	Run Time ¹ (h)	2.5 / 5 / 12	- / 1 / 3.5 / 25
₽ K	Color Temperature (K)	6000 - 7500	6000 - 7500
(CRI)	Color Rendering Index (CRI)	70	70
В	ATTERY AND CASE		
	Battery	1x Mignon (AA) Alkaline 1.5V	1x 14500 Li-ion Battery 3.7V
III P	Battery Capacity² (Wh / mAh)		2.77 / 750
φ	IP Level	IP44	IP68
(Rechargeable	No	Yes
Ð	Charging Time ⁵ (min)		120
<u>†</u>	Drop Height (m)	2	2
S	IZE AND WEIGHT		
<u></u>	Length – Defocused (mm)	120	123
\bigcirc	Head Diameter (mm)	26	29
g	Weight incl. battery (g / oz)	83 / 2.9	106 / 3.7
Т	ECHNOLOGY		
1	Smart Light Technology		•
	Flex Sealing Technology		•
<u></u>	Magnetic Charge System		•
	Temperature Control		•
	Advanced Focus System	•	•
	More Features	Dual Power Source, Rapid Focus	Dimmable, Transportation Lock, Flicker-free, Memory Mode, Backup Mode Emergency Light, Battery Indicator, Charge Indicator, Low Battery Warning
P	ACKAGING		
	Item no. Box / GTIN	502599 / 4058205028523	502178 / 4058205020428
	Content Box	1 Battery Set, Lanyard	1 Battery Set, Lanyard, Magnetic Charging Cable

502700 Lamp Adapter Type F

0337 Pouch Type D

P6 CORE	P6R CORE	
1x High Power LED	1x Xtreme LED	
Power / Low Power	Boost / Power / Mid Power / Low Por (+ Position, Blink, S.O.S., Strobe)	wer
300 / 25	900 / 600 / 240 / 15	
200 / 60	240 / 190 / 120 / 25	
3.5 / 25	- / 2 / 6 / 95	
6000 - 7500	6000 - 7500	
70	65	
3x Micro (AAA) Alkaline 1.5V	1x18650 Li-ion Battery 3.7V	
	9.25 / 2500	
IP54	IP68	
No	Yes	
	300	
2	2	
117	151	
32	35	
130 / 4.6	170 / 6.0	
	•	
	•	
	•	
	•	
•	•	
Energy Saving, Rapid Focus	Dimmable, Transportation Lock, Flicker-free, Memory Mode, Backup M Emergency Light, Temperature Cont System, Battery Indicator, Charge Indicator, Low Battery Warning	
502600 / 4058205028554	502179 / 4058205020459	
1 Battery Set, Lanyard	1 Battery Set, Lanyard, Magnetic Charging Cable	
	502250 Lamp Adapter Type C	

P5R CORE 03 01 - Extreme dust and water predection (IP68) 02 - Advanced Focus System - stepless focusing 03 - Flex Sealing Technology - can be used for a short time underwater (including the focusing system) to a depth of one meter **04** – Personalize the light functions via **Smart Light Technology 05** – Convenient and safe

charging the battery
thanks to the Magnetic
Charge System

06 - Constant Light - constant
luminous flux over a long

07 – **Flicker-free** constant light

enables optimal and safe

period

illumination

OPTIONAL ACCESSORIES

Further accessories on page 70

P7R CORE & Control of the control of

THE P-SERIES A TIMELESS CLASSIC













- 01 Extreme dust and water prodection (IP68)
- **02 Advanced Focus System** stepless focusing
- 03 Flex Sealing Technology can be used for a short time underwater (including the focusing system) to a depth of one meter
- **04 Multi-Core Optics** homogeneous beam made possible by special faceting of the lens
- **05** Personalize the light functions via **Smart Light Technology**
- 06 Integrated Battery and Charge Status Display
- 07 Convenient and safe charging of the battery thanks to the Magnetic Charge System







— P-SERIES CORE



L	ED
$\overline{\triangle}$	LED Configuration
वा॥	Light Functions
- <u>`</u> \.	Luminous Flux¹ (lm)
\Rightarrow	Beam Distance ¹ (m)
<u>(L)</u>	Run Time ¹ (h)
Ŋκ	Color Temperature (K)
(CRI)	Color Rendering Index (CRI)
В	ATTERY AND CASE
ш	Battery
1111-11	Battery Capacity ² (Wh / mAh)
\$	IP Level
٩	Rechargeable
ð	Charging Time ⁵ (min)
<u>↓</u>	Drop Height (m)
S	IZE AND WEIGHT
7	Length – Defocused (mm)
\bigcirc	Head Diameter (mm)
<mark>∕g</mark> \	Weight incl. Battery (g / oz)
T	ECHNOLOGY
111	Smart Light Technology
	Flex Sealing Technology
<u></u>	Magnetic Charge System
	Multi Core Optics
	Advanced Focus System

(CRI)
/ mAh)
nm)
-
/ oz)
39
gy
em
em
SORIES
SORIES
SORIES

×	Drop Height (m)
S	IZE AND WEIGHT
<u></u>	Length – Defocused (mm)
\bigcirc	Head Diameter (mm)
\g\	Weight incl. Battery (g / oz)
Т	ECHNOLOGY
(11)	Smart Light Technology
(i)	Flex Sealing Technology
<u></u>	Magnetic Charge System
	Multi Core Optics
	Advanced Focus System
	More Features
P	ACKAGING
	Item no. Box / GTIN
	Containt Day
	Content Box
0	PTIONAL ACCESSORIES
Fur	rther accessories on page 70





reddot winner 2021



P7 CORE



P7R CORE		P17R CORE
----------	--	-----------

1x Power LED	1x Xtreme LED	1x Xtreme LED
Power / Mid Power / Low Power	Boost / Power / Mid Power / Low Power (+ Position, Blink, S.O.S., Strobe)	Boost / Power / Mid Power / Low Power (+ Position, Blink, S.O.S., Strobe)
450 / 250 / 40	1400 / 1000 / 440 / 15	1200 / 900 / 350 / 15
300 / 220 / 100	300 / 210 / 130 / 15	560 / 420 / 270 / 50
1 / 2 / 25	- / 2 / 4 / 90	- / 2.75 / 12 / 200
6000 - 7500	6000 - 7500	6000 - 7500
70	70	65
4x Micro (AAA) Alkaline 1.5V	1x 21700 Li-ion Battery 3.7V	1x LiFePO4 Battery pack 6.4V
	17.76 / 4800	36.48 / 5700
IP54	IP68	IP54
No	Yes	Yes
	270	270
1	2	1
130	158	290
37	35	53
175 / 6.2	202 / 7.1	715 / 25.2
	•	•
	•	_
	•	•
	•	
•	•	•
Energy Saving, Rapid Focus	Dimmable, Transportation Lock, Flicker-free, Memory Mode, Backup Mode, Emergency Light, Temperature Control System, Battery Indicator, Charge Indicator, Low Battery Warning	Mode Switch, Dimmable, Transportation Lock, Flicker-free, Memory Mode, Backup Mode, Emergency Light, Safety Ytrion Cell, Rapid Focus, Battery Indicator, Charge Indicator, Low Battery Warning
502180 / 4058205020480	502181 / 4058205020510	502182 / 4058205020541
1 Battery Set, Lanyard	Battery Set, Lanyard, Magnetic Charging Cable	1 Set of Batteries, Intelligent Clip, Wall Mount, Power Adapter, Magnetic Charging Cable

502251 Lamp Adapter Type D

0042 Signal Cone 53 mm

1-8 Information on page 84

P6R CORE QC



- 01 Equipped with a


 Multicolor LED with white,
 red, green and blue light
- **02 Multicolor Strobe** colored flashes of light with irritating glare effect for emergencies
- **03 Easy Operation** the rotary switch enables quick color changes
- **04 Advanced Focus System –** stepless focusing





P6R CORE QC

	I OIL OOILE GO
LED	
△ LED Configuration	1x Power LED
Light Functions (weißes Licht)	Power / Mid Power / Low Power
-\(\rightarrow\)- Luminous Flux\(\text{1}\) (lm)	270 / 120 / 15
□→ Beam Distance¹ (m)	335 / 220 / 80
© Run Time ¹ (h)	5 / 14 / 110
Color Temperature (K)	6000 - 6500
© Color Rendering Index (CRI)	80 (white light)
BATTERY AND CASE	
■ Battery	1x Li-ion Battery 3.7V
■ Battery Capacity² (Wh / mAh)	9.25 / 2500
□ IP Level	IP54
(i) Rechargeable	Yes
Ĉ Charging Time⁵ (min)	300
Drop Height (m)	1.5
SIZE AND WEIGHT	
∠ Length – Defocused (mm)	157
Head Diameter (mm)	42
Weight incl. Battery (g / oz)	207 / 7.3
TECHNOLOGY	
Rapid Focus	•
Advanced Focus System	•
More Features	Multicolor Strobe, Singlecolor Strobe
PACKAGING	
Item no. Box / GTIN	502517 / 4058205026819
Content Box	1 Battery Set, Lanyard, Micro-USB Charging Cable
OPTIONAL ACCESSORIES	
	502251 Lamp Adapter Type D
Further accessories on page 70	502729 Remote Switch Type G




- P7R SIGNATURE

PREMIUM ILLUMINATION

















- 01 Powerful premium flashlight with Natural Light Technology (80 CRI / 6500K)
- **02 Mode Switch** for direct access to personalized light functions via Smart Light Technology
- **03** Additional **red secondary light** on the side of the housing, e. g. to maintain the night vision
- **04 Hard-anodized housing material** for additional protection against wear and corrosion
- 05 Extreme dust and water protection (IP68)
- **06 Flex Sealing Technology** can be used for a short time underwater (including the focusing system) to a depth of one meter
- **07** Personalize the light functions thanks to **Smart Light Technology**
- **08 Constant Light** consistent level of brightness over time
- 09 Integrated battery and charge status indicator



-**>** 2000 lm¹ — 330 m¹ —



90 h¹

MAXIMUM PERFORMANCE, STYLISH DESIGN













P6R SIGNATURE

P7R SIGNATURE

L	ED		
\bigcirc	LED Configuration	1x Xtreme LED, (1x red LED)	1x Xtreme LED, (1x red LED)
all	Light Functions	Boost / Power / Mid Power / Low Power (+ Position, Blink, S.O.S., Strobe, Red Light)	Boost / Power / Mid Power / Low Power (+ Position, Blink, S.O.S., Strobe, Red Light)
<u>-;Ċ</u> -	Luminous Flux¹ (lm)	1400 / 1100 / 450 / 15	2000 / 1200 / 500 / 15
□	Beam Distance ¹ (m)	240 / 190 / 110 / 20	330 / 200 / 130 / 20
<u>(L)</u>	Run Time ¹ (h)	- / 1.25 / 2.5 / 60	- / 2 / 3.25 / 90
- Ik	Color Temperature (K)	6000 - 7500	6000 - 7500
(RI)	Color Rendering Index (CRI)	80	80
В	ATTERY AND CASE		
	Battery	1x 18650 Li-ion Battery 3.6V	1x 21700 Li-ion Battery 3.7V
III.	Battery Capacity ² (Wh / mAh)	10.89 / 3000	17.76 / 4800
ф	IP Level	IP68	IP68
٩	Rechargeable	Yes	Yes
Ø	Charging Time ⁵ (min)	225	270
<u></u>	Drop Height (m)	2	2
S	IZE AND WEIGHT		
7	Length – Defocused (mm)	151	158
\bigcirc	Head Diameter (mm)	35	35
ß	Weight incl. Battery (g / oz)	170 / 6.0	202 / 7.1
Т	ECHNOLOGY		
1	Smart Light Technology	•	•
	Flex Sealing Technology	•	•
<u></u>	Magnetic Charge System	•	•
	Multi-Core Optics	•	•
	Advanced Focus System	•	•
	More Features	Red Alternate Light, Mode Switch, Emergency Light, Temperature Control, Dimmable, Transportation Lock, Flicker- free, Memory Function, Backup Mode, Emergency Light, Battery Indicator, Char- ge Indicator, Low Battery Warning	Red Alternate Light, Mode Switch, Emergency Light, Temperature Control, Dimmable, Transportation Lock, Flicker- free, Memory Function, Backup Mode, Emergency Light, Battery Indicator, Charge Indicator, Low Battery Warning
Р	ACKAGING		
	Item no. Box / GTIN	502189 / 4058205020756	502190 / 4058205020787
	Content Box	1 Set of Batteries, Leather Belt Pouch, Lanyard, Magnetic Charging Cable, Pocket Clip, USB Power Adapter, Wall Bracket	1 Set of Batteries, Leather Belt Pouch, Lanyard, Magnetic Charging Cable, Pocket Clip, USB Power Adapter, Wall Bracket



P18R SIGNATURE

3x Xtreme LED

Boost / Power / Mid Power / Low Power (+ Position, Blink, S.O.S., Strobe)

4500 / 2600 / 1000 / 30

720 / 420 / 260 / 50

- / 2.5 / 4.5 / 70

6000 - 7200

70

1x Li-ion Battery Pack 11.1V
33.3 / 3000
IP54
Yes
330

171

86

637 / 22.5

_

X-Lens Technology, Rapid Focus, Dimmable, Transportation Lock, Flicker-free, Memory Function, Backup Mode, Emergency Light, Battery Indicator, Charge Indicator, Low Battery Warning

502191 / 4058205020817

1Set of Batteries, Lanyard, USB Power Adapter, Magnetic Charging Cable

P-SERIES SIGNATURE





KEY RING LIGHTS















1/ /.	
N4	\boldsymbol{R}

	K4R
LED	
	1x Power LED
Light Functions	Boost / Power / Low Power
-\hat{\tau}- Luminous Flux1 (lm)	120 / 80 / 20
□→ Beam Distance¹ (m)	30 / 25 / 10
C Run Time ¹ (h)	- / 1 / 3.5
BATTERY AND CASE	
 	1x Li-ion Battery 3.7V
Battery Capacity ² (Wh / mAh)	0.67 / 180
(a) Rechargeable	Yes
Ĉ Charging Time⁵ (min)	180
P Level	IP2X
SIZE AND WEIGHT	
∠¹ Length (mm)	52
Width (mm)	25
Weight incl. Battery (g / oz)	20 / 0.7
FEATURES	
	Transportation Lock, Battery Indicator, Charge Indicator
PACKAGING	
Item no. Box / Gray	Gray: 502574 / 4058205029117
Item no. Box / Rosé-Gold	Rose Gold: 502575 / 4058205029148
Content Box	Carabiner, Key Ring









K6R Safety
1x High Power LED
Boost / Power / Low Power (+ Strobe)
400 / 200 / 20
80 / 50 / 15
- / 1.5 / 8
1x Li-ion Battery 3.7V
1.48 / 400
Yes
180
IP2X
66
30
32 / 1.1
Transportation Lock, Shrill Alarm, Battery Indicator, Charge Indicator
Safety Gray: 502580 / 4058205028370
Rose Gold: 502581 / 4058205028721
Carabiner, Key Ring, Wrist Strap

KIDSLIGHTS









KIDS LIGHTS LIGHT, FUN AND SAFETY

The Ledlenser KidsLights series lights specifically address the needs and requirements of children. They offer a wide range of uses, from the selfmade cave to the safe way to school, a multitude of colorful light functions, quick and easy operation, and practical energy-saving features. And, most importantly, safety always comes first. For instance, glaring effects and the luminous flux are reduced and all headlamps come with safety headbands which open automatically.



Versatile: white light, red light and blue light with optional flashing functions (red and blue)

Clever: Optics with reduced glaring for children's sensitive eyes

Energy-saving: automatic switch-off after 20 minutes (optional)



Practical: integrated metal clip for further attachment options without headband (e.g. on school satchel, backpack, clothing)



Safe: Pressure sensitive headband that releases automatically to prevent accidental injury



















L	ED		
\Box	LED Configuration	1x Power LED (White), 1x LED (Red), 1x LED (Blue)	1x Power LED (White), 1x LED (Red), 1x LED (Blue)
411	Light Functions	Power (White), Low Power (White), (Power (Red), Blink (Red), Power (Blue), Blink (Blue), Blink (Red / Blue))	Power (White), Low Power (White), (Power (Red), Blink (Red), Power (Blue), Blink (Blue), Blink (Red / Blue))
- <u>`</u> Ċ́-	Luminous Flux¹ (lm)	40 / 5	40 / 5
➾	Beam Distance ¹ (m)	9 / 2	9 / 2
<u>(L)</u>	Run Time ¹ (h)	1.5 / 20	2 / 18
В	BATTERY AND CASE		
	Battery	1 x AAA Alkaline 1.5V	1 x Li-ion 3.7V (intern)
ф	Battery Capacity ² (Wh / mAh)	-	1.036/280
III-1	Rechargeable	No	Yes
đ	Charging Time ⁵ (min)	-	60
ආ	IP Level	IPX4	IP56
S	SIZE AND WEIGHT		
\bigcirc	Durchmesser (mm)	54	37
g	Weight incl. Battery (g / oz)	35 / 1.2	25 / 0.9
F	EATURES		
		White Light, Red Light, Blue Light, Automatic Switch-Off (optional), Safety Headband, Metal Clip for Mounting as Clip Light	White Light, Red Light, Blue Light, Automatic Switch-Off (optional), Safety Headband, Metal Clip for Mounting as Clip Light, Charge Indicator
P	ACKAGING (BOX)		
	Item no. / GTIN	502537 (Green) / 4058205027038	502535 (Green) / 4058205026970
	Item no. / GTIN	502538 (Purple) / 4058205027069	502536 (Purple) / 4058205027007
	Content Box	1 Set of Batteries	Micro-USB Charging Cable

^{*} Caution: Not suitable for children under 36 months. Caution: Use under direct adult supervision.



KIDSLIGHTS







KIDBEAM4*

KIDCAMP6*

	.EU		
\triangle	LED Configuration	1x Power LED (White), 1x LED (Red), 1x LED (Blue), 1x LED (Green)	1x Power LED (White), 1x LED (Red), 1x LED (Blue), 1x LED (Green)
all	Light Functions	Power (White) / Low Power (White) (+ Power (Red), Power (Blue), Power (Green), Blink (Red und Blue))	Power (White) / Low Power (White) (+ Power (Red), Power (Blue), Power (Green), Blink (Red, Blue und Green))
- <u>`</u> Ċ;-	Luminous Flux¹ (lm)	70 / 10	60 / 10
	Beam Distance ¹ (m)	12 / 5	- / -
<u>(L)</u>	Run Time ¹ (h)	4 / 18	8 / 40
	BATTERY AND CASE		
	Battery	2 x AAA Alkaline 1.5V	3 x AAA Alkaline 1.5V
٩	Battery Capacity² (Wh / mAh)	-	
III-)ı	Rechargeable	No	No
Ō	Charging Time⁵ (min)	=	_
ф	IP Level	IP44	IP44
9	SIZE AND WEIGHT		
\bigcirc	Durchmesser (mm)	35	75
\g\	Weight incl. Battery (g / oz)	72 / 2.5	95 / 3.4
F	EATURES		
		White Light, Red Light, Blue Light, Green Light, Automatic Switch-Off (optional), Clip	White Light, Red Light, Blue Light, Green Light, Automatic Switch-Off (optional), Fold-Out Hook for Hanging Up the Light
E	PACKAGING (BOX)		
	Item no. / GTIN	502754 (Green) / 4058205030861	502753 (Green) / 4058205030847
	Item no. / GTIN	502789 (Purple) / 4058205031653	502786 (Purple) / 4058205031561
	Content Box	1 set of batteries	1 set of batteries

^{*} Caution: Not suitable for children under 36 months. Caution: Use under direct adult supervision.







KIDBEAM4 AAA Alkaline Batteries











Exploring with your first own flashlight:

The robust Kidbeam4 lights up in four different colors and impresses with practical, child-specific features such as the integrated clip or the automatic switch-off function.

KIDCAMP6 AAA Alkaline Batteries















For cozy evenings of playing or reading:

The Kidcamp6 provides the right mood and lights up in four different colors. It can be mounted in various ways thanks to the foldout hook, e. g. in a tent or caravan.



¹⁻⁸ Information on page 84

X-SERIES:

LIGHT FOR EXTREME NEEDS



-XP30R & ONE









L	ED	
\triangle	LED Configuration	30 x High Performance Automotive LEDs
иЩ	Light Functions	Boost, 5 Brightness Level (+ Strobe)
<u>-\\\</u>	Luminous Flux¹ (lm)	32,000 / 24,000 / 15,500 / 8500 / 4000 / 500
□>	Beam Distance ¹ (m)	>2000 / 1900 / 1500 / 1100 / 800 / 300
<u>(b)</u>	Run Time ¹ (h)	- / 0.5 / 0.75 / 1.25 / 2.5 / 16
В	ATTERY AND CASE	
	Battery	AMPShare Battery powered by BOSCH
III -1	Battery Capacity (Wh / mAh) ²	90 / 5000
٩	Rechargeable	Yes
đ	Charging Time ⁵ (min)	80
රු	IP Level	IP54
S	IZE AND WEIGHT	
<u></u>	B / H / T (mm)	307 x 212 x 180
g	Weight incl. Battery (g / oz)	3600 / 127
Т	ECHNOLOGY	
	Extreme Search Beam	•
	Active Cooling Technology	•
	Temperature Control	•
	More Features	Charge Indicator, Battery Indicator, Remote Control with up to 200 m range
Р	ACKAGING	
	Item no. Transport Case / GTIN	(EU version) 503039 / 4058205035798
		(UK version) 502783 / 4058205031264
	Contents	Hard Shell Transport Case, Battery System AMPShare - powered by Bosch, Battery Charger, Carrying Strap, Remote Control, Universal Mounting Bracket

1-7 Information on page 76

ULTIMATE LIGHT PERFORMANCE MADE IN GERMANY





- **01 High-end portable searchlight** with up to 32,000 lumens¹
- **Extreme Search Beam** 30 powerful automotive LEDs combined with unique optics for extreme long-range vision without glare at close range
- Active Cooling Technology powerful fan for maximum light output over a long period of time
- **AMPShare powered by Bosch battery** with fast charging function
- Compact dimensions and perfect weight distribution for optimal handling and single-handed operation
- Remote control with up to 200 m range
- 07 Extremely robust due to protective elements and robust front glass
- Screw thread for tripod mounting
- **Made in Germany** development and production in Germany according to highest quality standards





- **01 Extreme light output** up to 800 meters¹ beam distance with up to 5000 lumens¹ thanks to seven Xtreme LEDs
- **02 X-Lens Technology** precise synchronization of the bundles of rays from several reflector lenses to form an extremely homogeneous, stage-like floodlight or a very sharply focused high beam
- **03 Advanced Focus System** stepless focusing
- **04** High-quality battery system **Safety Ytrion Cell** over 5000 charging cycles without significant loss of capacity
- **05** Quick to hand convenient charging with the **Floating Charge System**
- **06 Great ease of use** 7 light functions, 4 light programs, 2 energy modes, and 1 multi-function switch



¹⁻⁸ Information on page

EXTREME POWERRECHARGEABLE & MULTIFUNCTIONAL



	2
LED	
	7x Xtreme LED
□Ⅲ Light Functions	Boost / Power / Low Power (+ Blink, S.O.S., Strobe, Position)
-\(\)- Luminous Flux¹ (lm)	5000 / 3500 / 200
□ Beam Distance¹ (m)	800 / 700 / 150
L Run Time ¹ (h)	- / 5 / 40
BATTERY AND CASE	
■ Battery	1x LiFePO4 Battery Pack 9.6V
Battery Capacity ² (Wh / mAh)	48 / 5000
(a) Rechargeable	Yes
Ĉ Charging Time⁵ (min)	210
□ IP Level	IP54
SIZE AND WEIGHT	
Length – defocused (mm)	405
Head diameter (mm)	95
Weight incl. Battery (g / oz)	1315 / 45.9
TECHNOLOGY	
Smart Light Technology	•
Rapid Focus	•
Floating Charge System	•
Advanced Focus System	•
X-Lens Technology	•
Emergency Light	•
Safety Ytrion Cell	•
Temperature Control	•
More Features	Energy Saving, Constant Light, Charge Indicator, Battery Indicator, Dimmable, Transportation Lock
PACKAGING	
Item no. Carrying Case / GTIN	501967 / 4058205015394
Contents	1 Battery Set, Floating Charge System, Assembly Material, Power Supply Unit, Roll Protection, Tripod Holder, Carrying Strap, Case
OPTIONAL ACCESSORIES	
	0386 Car Charger

1-8 Information on page 76




















- 02 Strong dust and water predection (IP67)
- **03** Stepless **swivel mechanism** for vertical alignment of the light cone
- **04 Advanced Focus System –** stepless focusing
- **05** Convenient and safe charging of the battery thanks to the **Magnetic Charge System**
- 06 Integrated battery and charge status indicator
- **07 Ledlenser Connecting System –** one interface for many accessories





—H-SERIES CORE





H5

CORE	H5R	CORI

LED		
LED Configuration	1x High Power LED	1x High Power LED
Ill Light Functions	Boost / Power / Low Power	Boost / Power / Low Power
-\rac{\dagger}{-\dagger}- Luminous Flux¹(lm)	350 / 200 / 15	500 / 300 / 15
□ Beam Distance¹ (m)	160 / 120 / 30	200 / 150 / 30
Bun Time¹ (h)	- / 2 / 20	- / 2 / 50
Color Temperature (K)	6000 - 7500	6000 - 7500
CRI Color Rendering Index (CRI)	70	70
BATTERY AND CASE		
■ Battery	2x Mignon (AA) Alkaline 1.5V	1x Li-ion Battery Pack 3.7V
Battery Capacity ² (Wh / mAh)	-	6.66 / 1800
O IP Level	IP67	IP67
Rechargeable	No	Yes
ি Charging Time⁵ (min)	-	210
□ Drop Height (m)	1.5	1.5
SIZE AND WEIGHT		
Head Diameter (mm)	32	32
Øg Weight incl. Battery (g / oz)	178 / 6.3	167 / 5.9
TECHNOLOGY		
Multi-Core Optics		
Flex Sealing Technology	•	•
Magnetic Charge System		•
Fusion Beam		
Advanced Focus System	•	•
More Features	Cooling Technology, Dimmable, Transportation Lock, Energy Saving	Cooling Technology, Temperature Control, Dimmable, Transportation Lock, Flicker-free, Memory Mode, Backup Mode, Battery Indica- tor, Charge Indicator, Low Battery Warning, Constant Light
PACKAGING		
Item no. Box / GTIN	502193 / 4058205020848	502121 / 4058205020879
Content Box	1 Set of Batteries	1 Set of Batteries, Magnetic Charging Cable
OPTIONAL ACCESSORIES		
Further accessories on page 72	502451 Transp. Silicone Headband	502256 Universal Mounting Bracket









H7R CORE	H15R CORE	H19R CORE
1x Xtreme LED	1x Xtreme LED	2x Xtreme LED
Boost / Power / Low Power	Boost / Power / Low Power	Boost / Power / Mid Power / Low Power
1000 / 600 / 15	2500 / 1000 / 20	3500 / 1600 / 800 / 200
250 / 200 / 25	250 / 170 / 20	300 / 230 / 150 / 80
- / 4 / 65	- / 5 / 80	-/4/7/20
6000 – 7500	6000 – 7500	6000 – 7500
70	70	70
1x 21700 Li-ion Battery 3.7V	1x Li-ion Battery Pack 7.4V	1x Li-ion Battery Pack 7.4V
17.76 / 4800	35.52 / 4800	35.52 / 4800
IP67	IP67	IP68
Yes	Yes	Yes
210	330	330
1.5	1.5	1.5
41	47	68
259 / 9.1	380 / 13.4	374 / 13.2
	•	•
•	•	-
•	•	•
	-	•
•	•	-
Cooling Technology, Temperature Control, Dimmable, Transportation Lock, Flicker- free, Memory Mode, Backup Mode, Battery Indicator, Charge Indicator, Low Battery Warning, Constant Light	Cooling Technology, Temperature Control, Dimmable, Transportation Lock, Flicker- free, Memory Mode, Backup Mode, Battery Indicator, Charge Indicator, Low Battery Warning, Constant Light	Temperature Control, Cooling Technology, Optisense Technology, Dimmable, Trans- portation Lock, Flicker-free, Memory Mode, Backup Mode, Battery Indicator, Charge Indicator, Low Battery Warning, Constant Light, Red Light
502122 / 4058205020909	502123 / 4058205020930	502124 / 4058205020961
1 Set of Batteries, Magnetic Charging Cable	1 Set of Batteries, Magnetic Charging Cable	1 Set of Batteries, Magnetic Charging Cable

502253 Belt Clip Type A

502256 Universal Mounting Bracket 1-8 Information on page 84

502262 21700 Li-lon Recharge. Battery

H19R SIGNATURE



















- **01 Fusion Beam** individually adjustable flood and spotlight for a unique light image with perfect illumination
- **02 Multi-Core Optics** homogeneous light image thanks to special faceting of the lens
- 03 Ledlenser Connect App and Bluetooth® remote control enable personalization and remote control of the light functions
- **04 Optisense Technology** automatic adaptation to the light conditions thanks to the integrated sensor
- 05 Extreme Dust and Water Protection (IP68)
- 06 Additional Red Light to maintain night vision
- **07** Stepless **Swivel Mechanism** for vertical alignment of the light cone
- **08 Ledlenser Connecting System** one interface for many accessory parts
- O9 Additional Content: 1. Bluetooth® remote control, 2. Battery,
 3. USB power adapter, 4. Magnetic charging cable, 5. Extension cable 6. Helmet connecting kit, 7. Helmet clips, 8. GoPro Adapter,
 9. Universal holder, 10. Stand holder ➤ Supplied in a soft case
- 10 Reflective Headband
















H7R SIGNATURE


H19R SIGNATURE

LED		
LLU		
△ LED Configuration	1x Xtreme LED	1x Xtreme LED
□Ⅲ Light Functions	Boost / Power / Low Power (+ Strobe, Positon, SOS und Blink)	Boost / Power / Mid Power / Low Power (+ Strobe, Positon, SOS und Blink)
-\(\overline{\cappa}\)- Luminous Flux\(\text{1}\) (lm)	1200 / 700 / 15	4000 / 1800 / 800 / 200
□→ Beam Distance¹ (m)	260 / 220 / 25	330 / 250 / 150 / 80
© Run Time ¹ (h)	- / 3.5 / 65	- / 3.5 / 7 / 20
Color Temperature (K)	6500	6500
© Color Rendering Index (CRI)	80	80
BATTERY AND CASE		
ma Battery	1x 21700 Li-ion Battery 3.7V	1x Li-ion Battery Pack 7.4V
Battery Capacity ² (Wh / mAh)	17.76 / 4800	35.52 / 4800
P Level	IP67	IP68
Rechargeable	Yes	Yes
Charging Time ⁵ (min)	210	330
<u>↓</u> Drop Height (m)	1.5	1.5
SIZE AND WEIGHT		
Head Diameter (mm)	41	68
Weight incl. Battery (g / oz)	259 / 9.1	374 / 13.2
TECHNOLOGY		
Fusion Beam		•
Flex Sealing Technology	•	
Magnetic Charge System	•	•
Temperature Control	•	•
Advanced Focus System	•	
More Features	Cooling Technology, Emergency Light, Bluetooth®8, Dimmable, Transportation Lock, Flicker-free, Memory Mode, Backup Mode, Battery Indicator, Charge Indicator, Low Battery Warning, Constant Light	Mutli-Core Optics, Red Light, Optisense, Cooling Technology, Emergency Light, Bluetooth®8, Dimmable, Transportation Lock, Flicker-free, Memory Mode, Backup Mode, Battery Indicator, Charge Indicator, Low Battery Warning, Constant Light
PACKAGING		
Item no. Box / GTIN	502197 / 4058205021081	502198 / 4058205021111
Content Soft Case	1 Set of Batteries, Helmet Clips, Adapter for GoPro, Helmet Holder, Hook-and-Loop straps, Adhesive Pads, Magnetic Charging Cable, Tripod Holder, USB Power Adapter, Universal Holder, Extension Cable	Bluetooth® remote control, 1 Set of Batteries, Helmet Clips, Adapter for GoPro, Helmet Holder, Hook-and-Loop straps, Ad esive Pads, Magnetic Charging Cable, Tripod Holder, USB Power Adapter, Universal Holder, Extension Cable, Adhesive Pads
OPTIONAL ACCESSORIES		

502451 Transparent Silicone Headband

502256 Universal Mounting Bracket











NEO1R

∴ 250 lm¹ © 15 h¹ 39 g






ULTRALIGHT AND VERSATILE



night vision capability



BRIGHT ALLROUNDER FOR SPORTY MISSIONS



Tilting lamp head for individual adjustment of the light cone

NE03

-;; 400 lm¹ ⊙ 20 h¹



Perfect light pattern for fast-moving activities with combined close and long distance light



Tilting lamp head for individual adjustment of the light cone



Minimalist, ergonomic design with cable tunnel for perfect fit and wearing; 360° visibility thanks to red flashing rear light; easy operation with three AAA batteries

NEO5R





Perfect light pattern for fast-moving activities with combined close and long distance light



COMPACT POWER FOR AMBITIOUS ATHLETES

360° visibility thanks to red flashing rear light and reflective headband; quick and easy battery charging via Magnetic Charge System with status LED




Tilting lamp head for individual adjustment of the light cone

NEO9R de la companya de la companya

-;; 1200 lm¹ ⑤ 120 h¹









THE PERFECT LIGHT FOR TRAIL RUNNERS

status LED



Extremely powerful, replaceable battery pack; rechargeable via Magnetic Charge System with



Ergonomic design with removable overhead strap for perfect fit and wearing comfort during outdoor activities: included chest belt as additional attachment option

1-8 Information on page 176





-NEO-SERIES














NE01R

		NEO1R
L	ED	
$\overline{\triangle}$	LED Configuration	1x High Power LED
all	Light Functions	Boost / Power / Low Power
<u>-\\\</u>	Luminous Flux¹ (lm)	250 / 150 / 20
➾	Beam Distance ¹ (m)	80 / 50 / 15
<u>(L)</u>	Run Time ¹ (h)	-/3/15
В	ATTERY AND CASE	
	Battery	1x Li-ion Battery Pack 3.7 V
III-I	Battery Capacity ² (Wh / mAh)	2.7 / 730
P	Rechargeable	Yes
Ð	Charging Time ⁵ (min)	180
တ္	IP Level	IP67
S	IZE AND WEIGHT	
\bigcirc	Head Diameter (mm)	48
ğ	Weight incl. Battery (g / oz)	39 / 1.4
Т	ECHNOLOGY	
O	Fusion Beam	
<u></u>	Magnetic Charge System	•
	Temperature Control	•
	More Features	Low Battery Warning, Battery Indicator, Charge Indicator, Red Light, Transportation Lock, Backup Mode
Р	ACKAGING	
	Item no. Box / GTIN	502713 Blue / 4058205029971
	Item no. Box / GTIN	502720 White/Green /4058205030168
	Item no. Box / GTIN	502712 Black / 4058205029957
	Content Box	Magnetic Charging Cable
0	PTIONAL ACCESSORIES	

0332 Pouch Type H


0332 Pouch Type H

Further accessories on page 72



0332 Pouch Type H

502823 2x18650 Li-ion Rech. Bat. Pack





The CU2R can be easily used as a **BACKLIGHT FOR MANY** headlamps

for example e. g. HF-Series (p. 9) or NEO1R (p. 54)









)

LEU	
△ LED Configuration	1x Power LED (White), 2x LED (Red)
메 Light Functions	Power (White), Low Power (White), (+ Power (Red), Blink (White), Blink (Red))
-\rac{\tau}{-\tau}- Luminous Flux¹ (lm)	40 / 5
□ Beam Distance¹(m)	9 / 2
(L) Run Time ¹ (h)	2 / 18

Run Time ¹ (h)	2 / 18
BATTERY AND CASE	
Battery	1 x Li-ion 3.7V (internal)
Battery Capacity ² (Wh / mAh)	1036 / 280
(a) Rechargeable	Yes
ि Charging Time⁵ (min)	60
1P Level	IPX4
SIZE AND WEIGHT	
Battery Capacity ² (Wh / mAh) Rechargeable Charging Time ⁵ (min) IP Level	1036 / 280 Yes 60

O Durchr	messer (mm)	37
o y Weight	incl. Battery (g / oz)	25 / 0.9
FEATUR	RES	

Additional White and Red Flashing Light, Metal Clip for Attachment as Clip Light, Transportation Lock, Wrist Strap


PACKAGING (BUX)	
Item no. / GTIN	502730 / 4058205030366
Content Box	Micro-USB Charging Cable, Wrist Strap

¹⁻⁸ Information on page 84

CU2R is your trusted light partner that provides extra everyday safety in dim conditions and beyond – whether it's on a walk with the dog, on an evening run during rush hour or in everyday life as a rear light on clothing or backpack.

- 01 Compact, lightweight and versatile signal light with reflective wristband to increase safety in the dark
- 02 **One white LED and two extra bright red LEDs** offering two modes (power, blink)
- 03 Intuitive operation with two separate switches for white light and red light
- 04 Elastic strap with hook-and-loop closure and metal clip for quick and flexible attachment, e. g. on upper arm,

clothing or backpack





OUTDOOR LANTERNS



ML6 CONNECT WL se desple











- 01 Micro Prism Technology patented4 lens technology for glare-free light and high energy efficiency
- 02 Ledlenser Connect App and wireless Bluetooth® remote control enable personalization and remote control of the light functions
- 03 Infinitely dimmable via three-way switch
- 04 Powerbank function with USB connection for charging electronic devices
- **05 Red light** to maintain night vision ability
- **06** Rubber hook for hanging the light, integrated magnet for mounting it on metal surfaces, and a removable stand with a built-in metal hook that can be flipped out to provide more light mounting options
- **07** Convenient and safe charging via Magnetic Charge System
- **08** Integrated battery and charge status indicator

GLARE-FREE 360° ILLUMINATION WITH REMOTE CONTROL











ML-SFRIFS












502271 USB Adapter 2.4A





502271 USB Adapter 2.4A



502126 Flex3 Powerbank















ML6 Connect WL ML₆ ML6 Warm Light

14160	MEO Walli Light	MEO COMMECT WE
18x Power LED, 6x LED Rot	18x Power LED, 6x LED Rot	18x Power LED, 6x LED Rot
Boost / Power / Low Power (+ Blink, Pulse, S.O.S., Strobe, all functions also in red)	Boost / Power / Low Power (+ Blink, Pulse, S.O.S., Strobe, all functions also in red)	Boost / Power / Mid Power / Low Power (+ Blink, Pulse, Position, Strobe, S.O.S., Alpine emergency signal, all functions also in red)
750 / 550 / 5	750 / 550 / 5	750 / 550 / 100 / 5
-	-	- -
- / 4 / 240	- / 3.5 / 200	- / 3.5 / 12 / 180
1x 18650 Li-ion Battery 3.6V	1x 18650 Li-ion Battery 3.6V	1x 18650 Li-ion Battery 3.6V
10,89 / 3000	10.89 / 3000	10.89 / 3000
Yes	Yes	Yes
300	300	300
IP66	IP66	IP66
42	42	45
178	178	178
280 / 9.9	280 / 9.9	260 / 9.2
•	•	•
•	•	•
•	•	•
		•
Low Battery Warning, Charge Indicator, Battery Indicator, Dimmable, Transporta- tion Lock, Red Light, Memory Mode	Low Battery Warning, Charge Indicator, Battery Indicator, Dimmable, Transporta- tion Lock, Red Light, Memory Mode	Low Battery Warning, Charge Indicator, Battery Indicator, Dimmable, Transporta- tion Lock, Red Light, Bluetooth®, Memory Mode, Emergency Light
500929 / 4058205011259	502084 / 4058205017916	502201 / 4058205021203
1 Set of Batterie, Stand, Transport Bag, Micro-USB Cable	1 Set of Batterie, Stand, Transport Bag, Micro-USB Cable	1 Set of Batterie, Stand, Transport Bag, Magnetic Charging Cable

502126 Flex3 Powerbank

502126 Flex3 Powerbank

1-8 Information on page

Further accessories on page 72

PORTABLE ENERGY FLEX-SERIES







FLEX-SERIES: THE FUTURE OF PORTABLE ENERGY



	► FOR	21700	BATTERIES	FI	_EX
--	-------	-------	------------------	----	-----

	 _	·/	4	-	
-	 E)	X	- 1		П
	 	/\			

FOR 21700 BATTERIES	FLEX5	FLEXIU
TECHNICAL SPECS	Powerbank+	Powerbank+
∠ ⁷ Length (mm)	103	120
←→ Width (mm)	41	54
🕽 Height (mm)	28	29
Weight with Battery (g / oz)	126 / 4.4	235 / 8.3
Weight without Battery (g / oz)	55 / 1.9	164 / 5.8
TECHNOLOGY		
□ Battery	1x 21700 Li-ion Battery 3.7V	2x 21700 Li-ion Battery 3.7V
■ Battery Capacity² (Wh / mAh)	16.65 / 4500	33.30 / 9000
Ф IP Level	IP65	IP65
(a) Rechargeable	Yes	Yes
the Charging Time⁵ (min)	140	240
Energy Status	Battery Indicator, Charge Indicator, Low Battery Warning	Battery Indicator, Charge Indicator, Low Battery Warning
FEATURES	6-IN-1	6-IN-1
	Powerbank with replaceable battery	Powerbank with replaceable battery
	2. IP65 – water and dust protection	2. IP65 – water and dust protection
	Battery Charger (up to 30 % shorter charging time – compared to charging in a P7R CORE / WORK / SIGNATURE)	Battery Charger (up to 30 % shorter charging time – compared to charging in a P7R CORE / WORK / SIGNATURE)
	4. Safe Battery Storage	4. Safe Battery Storage
	5. Double protection against short circuit (box and battery)	Double protection against short circuit (box and battery)
	6. Battery Charge Indicator	Battery Charge Indicator for both batteries
MATCHES		
	H7R Core, H7R Signature, P7R Core, P7R Signature	H7R Core, H7R Signature, P7R Core, P7R Signature
PACKAGING		
Item no. Box / GTIN	502511 / 4058205026697	502127 / 4058205019286
Content	1 Rechargeable Battery, USB Cable (USB-A to USB-C)	2 Rechargeable Batteries, USB Cable (USB-A to USB-C)















Powerbank – new portable power Innovative 6-in-1-System

Flexible, sustainable, powerful – that distinguishes our new Flex series; the ideal addition for all outdoor activities.

The rechargeable batteries of the new Ledlenser powerbanks can be removed at any time and are easy to swop out after being drained.

Therefore, the powerbanks can charge the 18650 respectively 21700 batteries used in compatible Ledlenser lights and in other electronic devices.





(USB Type-A to Type-C) Micro-USB cable included



1-8 Information on page 76

FLEX-SERIES: EVEN MORE POWER ON THE GO



		. ==/(
T	ECHNICAL SPECS	Powerbank+	Powerbank+
7	Length (mm)	109	109
\longleftrightarrow	Width (mm)	27	47
Ĵ	Height (mm)	27	27
g	Weight with Battery (g / oz)	88 / 3.1	164 / 5.8
g	Weight without Battery (g / oz)	40 / 1.4	116 / 4.1
T	ECHNOLOGY		
	Battery	1x 18650 Li-ion Battery 3.6V	2x 18650 Li-ion Batteries 3.6V
111>1	Battery Capacity ² (Wh / mAh)	12.34 / 3400	24.68 / 6800
රු	IP Level	IP65	IP65
٩	Rechargeable	Yes	Yes
Ð	Charging Time ⁵ (min)	240	240
	Energy Status	Battery Indicator, Charge Indicator, Low Battery Warning	Battery Indicator, Charge Indicator, Low Battery Warning
	CATUDEC	/ INI 1	/ INI 1

1.	Powerbank with replaceable
	battery

- battery
 2. IP65 water and dust protection
- 3. Battery Charger (up to 30 % shorter charging time compared to charging in a P6R CORE / WORK / SIGNATURE)
- 4. Safe Battery Storage
- 5. Double protection against short circuit (box and battery)
- 6. Battery Charge Indicator

6-IN-1

- 1. Powerbank with replaceable battery
- 2. IP65 water and dust protection
- 3. Battery Charger (up to 30 % shorter charging time compared to charging in a P6R CORE / WORK / SIGNATURE)
- 4. Safe Battery Storage
- 5. Double protection against short circuit (box and battery)
- 6. Battery Charge Indicator for both batteries


MATCHES


► FOR 18650 BATTERIES

P6R Core, P6R Signature


P6R Core, P6R Signature

PACKAGING		
Item no. Box / GTIN	502126 / 4058205019255	502125 / 4058205019224
Contents Box	1 Rechargeable Battery, Micro-USB Cable	2 Rechargeable Batteries, Micro-USB Cable












ACCESSORIES FLASHLIGHTS

C = Core S = Signature

Item no.	MODEL	P2R C	P3 C	P4 C	P4R C	P5 C	P5R C	P6 C
0337	Pouch Type D	•	•			•		
502249	Lamp Adapter Type B						•	
0362	Universal Mounting System							•
501025	Remote Switch Type E							•
0380	USB Car Charger	•			•		•	
502271	USB Adapter 2.4A	•			•		•	
502265	Magnetic Charging Cable Type A						•	
502259	Charging Station Type A						•	
502596	Li-lon direct USB Rech. Battery 3.6 V / 880 mAh						•	
500985	14500 Li-lon rechargeable battery 750 mAh					•	•	



Item no.	MODEL	P17R C	P18R \$
0042	Signal Cone 53 mm Orange	•	
0380	USB Car Charger		•
502271	USB Adapter 2.4A		•
502265	Magnetic Charging Cable Type A		•



Diverse Item no.

The plastic plug-in attachment quickly transforms a flashlight into a versatile red signal light at any time, e.g. for signal light





ltem no.	MODEL	P6R C	P7 C	P7R C	P6R C QC	P6R S	P7R S
0333	Pouch Type A		•				
0342	Pouch Type G			•	•	•	•
502269	Leather Pouch Type D			•			•
0323	Tactical Professional Holster Type B		•	•			•
502250	Lamp Adapter Type C	•					
502251	Lamp Adapter Type D			•	•		•
0317	Intelligent Clip Type C		•				
0362	Universal Mounting System	•	•	•	•		•
501033	Magnetic Mount	•	•	•	•	•	•
502237	Signal Cone 35.1mm Orange	•		•		•	•
0040	Signal Cone 37mm Orange		•				
502238	Color Filter Set 35.1mm	•		•		•	•
502729	Remote Switch Type G				•		
0380	USB Car Charger	•		•	•	•	•
502271	USB Adapter 2.4A	•		•	•	•	•
502265	Magnetic Charging Cable Type A	•		•		•	•
502260	Charging Station Type B	•		•		•	•
502262	21700 Li-ion Rechargeable Battery 4800mAh			•			•
502595	Li-Ion direct USB Rechargeable Battery 3.6 V / 2500 mAh	•			•	•	
502126	Powerbank Flex3	•			•	•	
502125	Powerbank Flex7	•			•	•	
502511	Powerbank Flex5			•			•
502127	Powerbank Flex10			•			•
501001	Li-Ion Rechargeable Battery 3.6 V / 3000 mAh	•			•	•	



Intelligent Clip Practical belt clip for attachment to the pants, can be rotated 360 rotated

Item no. 0317

Item no. 502262 **Charging Station** Professional charging station incl. magnetic charging cable, compatible with 5 Station Charging Panel



Item no. 0362 Universal Mounting System

This universal mounting fixes flashlights with a diameter of 25-34 mm securely to tripods, rods and tubes in next to no time. The light and fixation are aligned in parallel











Four high quality color filters: Red maintains night vision ability. Green and red are suitable for animal observation, among other things. Yellow improves visibility in fog. Blue improves the visibility of liquids

Item no. 502269 Leather Pouch durable leather protective bag



ACCESSORIES HEADLAMPS

C = Core S = Signature

Item no.	MODEL	HF4R C	HF6R C	HF8R C	H5 C	H5R C	H7R C	H15R C	H19R C
0332	Pouch Type H	•	•	•	•	•			
502253	Belt Clip Type A							•	•
502314	Helmet Connecting Kit Type H	•	•	•	•	•	•	•	•
502313	Helmet Band Fixing Clip Type A				•	•	•	•	•
502256	Universal Mounting Bracket Type E	•	•	•	•	•	•	•	•
502451	Transparent Silicone Headband Type A				•	•	•	•	•
502469	Headband+Overheadband Core				•	•	•	•	•
502311	Bluetooth®8 Remote Control Type A			•					
502271	USB Adapter 2.4A						•	•	•
502265	Magnetic Charging Cable Type A	•	•	•			•	•	•
502312	Extension Cable Type C							•	•
502262	21700 Li-ion Recharge. Battery 4800mAh						•		
502411	Bluetooth®8 2x 21700 Batterybox							•	•
502511	Powerbank Flex5						•		
502127	Powerbank Flex10						•		
502310	2x 21700 Li-lon Recharge. Battery Pack							•	•
502929	USB-C Adapter 20W	•	•	•					




Item no. 502314 **Helmet Connecting** Kit Type H Stable helmet holder system for a wide variety

of helmet models





Item no. 502256 **Universal Mounting Bracket** Stable universal fastening



Item no. 502312

Extension Cable


backpack

Practical extension cable (120 cm)

head and the battery box - so the battery can easily be stowed in the

that is plugged in between the lamp









Item no. 502265 **Magnetic Charging Cable** Magnetic charging cable with standard USB-A connector

POWERBANK FLEX 10

ACCESSORIES LANTERNS














LEDLENSER TECHNOLOGY ABC

From innovative lenses and advanced light functions to future-oriented power supplies - we work tirelessly to improve our technology to further expand our lead. Here are some examples:



ADVANCED FOCUS SYSTEM (AFS)

Galileo swore by the power of lenses; Newton by the power of reflectors. We have simply combined the two Technologies – only better than anyone before. The result: our patented Advanced Focus System (AFS), which allows a seamless transition from homogeneous low beam to sharply focused high beam.





ADAPTIVE LIGHT BEAM

extended battery runtime.

Our Adaptive Light Beam technology dims and focuses automatically. This way, the light is adapted to changing environments and obstacles; from uneven forest ground and wet sidewalks to narrow machine compartments – without manual control. The system detects blinding reflections as well as overall light conditions and controls all light sources separately. This does not only result in an ideal illumination


and focusing, but it also enables completely hands-free use, with an



fii

COOLING TECHNOLOGY

Cooling Technology (CT) ensures your head stays cool even when your light is at maximum power. Our CT products reduce LED heat to the optimal level by means of the intelligent use of cooling elements. This technology is also used to cool computer chips and ensures highly efficient use of energy, increased illuminating power, and especially long-lasting LEDs.





ACTIVE COOLING TECHNOLOGY

High luminosity requires special measures. A powerful fan actively cools down the high-end LED and allows maximum light output over long periods of time – while remaining consistently energy-efficient.





DUAL POWER SOURCE


Our Dual Power Source allows you to use the full performance of your Ledlenser at any time – no matter what power source you have available. This technology recognizes the power source and you can therefore. You can therefore choose between the rechargeable Ledlenser battery or a disposable battery. Extremely practical for long trips without a power point.





DIGITAL ADVANCED FOCUS SYSTEM

Our patent-pending Digital Advanced Focus System (dAFS) allows a virtually seamless transition from homogeneous floodlight to focused spotlight. Its efficiency delights even experts. The technology enables a slim design, ideal lighting for different ranges and permanent peripheral vision.





EMERGENCY LIGHT

This feature turns your flashlight into an emergency light: If the power goes out while your Ledlenser is on the charging base, it will automatically turn on. So the light helps you find your way around, e. g. to the breaker panel.





EXTREME SEARCH BEAM

Our Extreme Search Beam consists of several powerful LEDs and a unique optical system for extreme long-range vision. The light is sharply focused to prevent glare at close range. The ultimate light beam for long-range vision.





FLOATING CHARGE SYSTEM

Grab-and-go wireless charging. The Floating Charge System is a wall-mounted magnetic charging system, getting the light ready to go with a simple flick of the wrist. It also offers USB charging with an adapter system that can be plugged into standard outlets or car lighters.







FLEX SEALING TECHNOLOGY


The innovative Flex Sealing Technology ensures that the electronic parts of the lamp head are completely sealed off, to protect against the penetration of water and dust. This flexible System is used. The focus can even be used underwater.





RAPID FOCUS

When focusing or defocusing the flashlight or headlamp, the reflector lens moves in relation to the LED. To ensure this process is as quick and ergonomic as possible we developed Rapid Focus: a single-hand mechanism that allows the light beam to be adjusted as fast as lightning.





FUSION BEAM

By combining different LEDs and lenses, lights with Fusion Beam have a unique, application-optimized illumination. This simultaneously enables a homogenous close-up wide flood beam and sharply focused long-distance beam. The intensity of the flood and spot beams can be individually adjusted thanks to independent controls for each light source.



SAFETY YTRION CELL


Ledlenser's Safety Ytrion Cell is a special lithium iron phosphate battery with unique properties: The technology combines high energy density with superior durability and safety, even in rough use and adverse storage conditions.





MAGNETIC CHARGE SYSTEM


With the Magnetic Charge System, the charging cable can quickly and easily be attached to the light. The connection for charging the battery is made via magnetic contacts. When the contacts approach each other, the charging cable automatically pairs with the light. The connection is automatically released under load.





SMART LIGHT TECHNOLOGY (SLT)

This innovation turns a Ledlenser into your personal lighting tool: A micro-controller allows individual ranges of functions to be programmed to different touch and switch combinations. That way, you always have the perfect light mode at hand.







MULTI-CORE OPTICS

Multi-Core Optics harness and direct the light emitted from extremely powerful, next-generation LEDs. The special faceted lens tames and directs the light, resulting in a homogeneous beam and aesthetic illumination.





TEMPERATURE CONTROL

Our lights stay cool, even when they work hard. Thanks to the intelligent and fully automated temperature control, a Ledlenser never gets too hot, no matter how much it is used. This protects you from burns and the LED from overheating.





NATURAL LIGHT

In certain situations the perceived color of light differs. Ledlenser therefore not only supplies extremely bright, but also extremely natural (CRI) over 90. This ensures true color rendering, even in the deep red color range.







X-LENS TECHNOLOGY

This technology is an enhancement of the Advanced Focus System. It can merge virtually any number of reflector lenses and synchronizes their individual light beams into a perfect beam, resulting in a high-grade, homogeneous floodlight in unfocused mode and our most sharply focused high beam to date.





LEDLENSER

IT TAKES EIGHT MINUTES FOR THE LIGHT OF THE SUN TO REACH THE EARTH – OURS ONLY TAKES THE PUSH OF A BUTTON

The sun and Ledlenser have something in common: We create light for the whole world! We are devoted to this task with all our energy and capability. The quality products made by Ledlenser prolong daylight and therefore, enable being active when dusk sets in or even during total darkness. They bring light into the darkest corners and in doing so, enable precise and professional work at any time.

WHAT DISTINGUISHES US

- One of the global market leaders in portable lights. That includes: Flashlights, headlamps, work lights, floodlights, lanterns, EX-protected lights
- > "German Engineering & Design": In-house development, production and quality assurance
- > Inventor of the trendsetting and patented³ Advanced Focus System
- > 7-year warranty⁴ for most products in connection with online registration
- More than 100 industrial property rights as well as more than 200 awards and prizes for our products
- > More than 650 employees worldwide
- Company-owned offices in Germany, China, USA, Yespan, Denmark, United Kingdom, Italy and Switzerland
- > Worldwide collaboration with more than 30 master distributors

OUR PRODUCTION PLANT IN CHINA

To ensure that our bright ideas see the light of day, we clearly divided up our tasks: "Engineered in Germany, produced in China". Our production expertise is concentrated at our location in Yangjiang, Guangdong. Every product is manufactured and tested here; from prototype to mass production.

The checklist for quality control includes 24 tests: Endurance, extreme temperatures, water, salt, impact, pressure and more - inspected and tested until the products have overcome all obstacles and meet our quality standards. Furthermore, it is important to us to take responsibility for our employees in China. We do this for example by building company housing and through our involvement in social and intercultural projects.







MORE THAN 20 YEARS OF EXPERTISE IN LIGHTING SOLUTIONS

When the two brothers Harald and Rainer Opolka from Solingen started out, they really didn't have much more than a garage, an old Atari computer, a set of tools, a drawing pad and around 1000 Deutschmarks of seed capital. Today, the former garage company of both the Ledlenser founders is an internationally operating company and one of the global market leaders in portable lights. The German Ledlenser brand conquered the flashlight market in the year 2000. The approach of equipping a flashlight with an LED instead of a bulb as a light source was absolutely visionary at that point in time. Millions of the "V8 Photon Pump" were sold worldwide and it constituted a new era of portable light – the "P7" achieved the same thing several years later.

To meet our objective as an LED pioneer, we are still using this technological advantage today in the development of new products – particularly in times during which LED lighting has become the norm in so many places and genuine quality is becoming harder and harder to recognize. At the same time, our premise "German Engineering & Design" has guided us from day one and justifies our unique commitment to quality. Ledlenser products give users worldwide the freedom of doing their jobs to the best of their ability or pursuing their passion with devotion – with the best possible light on their side.



LEDLENSER GUARANTEED QUALITY









Management System ISO 9001:2015 ISO 14001:2015 ISO 50001:2018

www.tuv.com ID 9108640713

QUALITY

"German Engineering & Design" - this statement stands for the highest development and production standards in regard to technology, design, materials and workmanship. We hold more than 100 industrial property rights. These include patents, utility models and designs. We are proud of having received various design awards for our products.

WARRANTY

Since we are confident in the quality of our lights, we grant a seven-year warranty on nearly all products in connection with online registration. All original Ledlenser products covered by our warranty include a product registration card. To register, simply scan the QR code with a smartphone or enter the indicated URL on your laptop or PC.

ISO CERTIFICATION

We meet the requirements of the ISO 9001, ISO 14001 and ISO 50001 standards and are certified by $T\ddot{U}V$ Rheinland.

Quality management: DIN EN ISO 9001:2015

Our systematic quality management ensures a consistently high quality of our products and services. Clearly defined and comprehensible processes enable us to meet our customers' expectations consistently and professionally. We also meet the standard requirements at our Chinese location.

Environmental management: DIN EN ISO 14001:2015

Our company has defined an internal environmental policy and precise environmental objectives. Here, the focus is on the establishment and realization of an environmental management system, to ensure continuous improvements – e. g. in regard to $\rm CO_2$ emissions, the use of resources and other environmental factors.

Energy management: DIN EN ISO 50001:2018

We operate energy management geared towards sustainability. This includes measures to reduce the consumption of energy such as electricity, gas and fuel as well as specific risk prevention.





— NOTES

The information pertaining to package contents, appearance, performance, dimensions and weight corresponds to the information available at the time of publication. In the interest of product development, we reserve the right to change package contents, appearance, design and color without prior notice. Product images may vary from the actual products and may show optional accessories which can be purchased separately. Errors and misprints excepted.

- 1) Measurements according to ANSI FL1 on the respective setting. If no setting is explicitly indicated, the values refer to luminous flux (Lumen/lm) and beam distance (meters/m) on the highest setting and to the run time (hours/h) on the lowest setting. If the light is equipped with color LED(s), the measurements indicated apply to white light or white LED. A boost function (if applicable) can be used several times, but only for short periods of time. If the light has different energy modes, measurement is based on "energy saving mode."
- 2) Calculated capacity value in watt-hours (Wh) or milliampere hours (mAh). This applies to the delivery state of the battery/ies inside the respective item, or for lights with rechargeable battery/ ies, to the rechargeable battery/ies inside the product when fully charged
- 3) EP Patent 1880139; US Patent 7,461,960

4) Two year warranty from the date of purchase, or seven years with online registration through our website. The warranty applies worldwide; legal warranty rights also apply. It covers defects in material and manufacture. Battery packs are guaranteed to work correctly for 24 months. This warranty does not cover products in the "Solidline" series, the LiteWallet®, the Powercase, the Batterybox7, the Kidled-Series also the Ledlenser K-Serie (except K3),, as well as defective batteries, holsters, pouches, remote switches, color filters, imprints and surface coatings. The warrantor is Ledlenser GmbH & Co. KG, Kronenstr. 5-7, 42699 Solingen, Germany. For more information visit ledlenser. com/warranty

- 5) The average charging time of the batteries in the delivery state in minutes may vary depending on the power supply unit used.
- 6) Additional talk time using the example of an iPhone X when charging with the fully charged batteries contained in the content of the article in question.
- 7) EP-Patent 3376097
- 8) The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of these by Ledlenser GmbH & Co. KG is under license

You can find our terms and conditions at www.ledlenser.com

Ledlenser GmbH & Co. KG

Kronenstraße 5-7, 42699 Germany, Deutschland

USt-IdNr.: DE815242425, Amtsgericht Wuppertal, HRA 23078

Personally liable partner: Ledlenser Beteiligungs GmbH

Headquarters: Solingen, Deutschland Amtsgericht Wuppertal, HRB 24774

Executive Director: Michael Reuter, Kai Milewski

- LEDLENSER WE'RE LOOKING FORWARD TO HEARING FROM YOU

We are always looking for ways to improve our support for you and your customers. We greatly appreciate any feedback you have on how we can build the Ledlenser brand together.

CONTACT MARKETING

Get answers to marketing questions and approval of marketing materials at:

CONTACT SALES GERMANY vertrieb@ledlenser.com

CONTACT TECHNICAL SUPPORT

For uncomplicated and fast processing, please contact our Consumer Care Team for all services, product, warranty and goodwill questions.

Customers from Germany can reach us by e-mail: support@ledlenser.com

Customers from Belgium, the Netherlands and Luxembourg can reach us by e-mail: service.bnl@ledlenser.com

Customers from Austria can reach us by e-mail: support@ledlenser.at

Customers from Switzerland can reach us by e-mail: office@ledlenser.ch









