LEDLENSER



















LIFESTYLEPRODUCT CATALOG











Ledlenser believes that a simple beam of light can empower the world. It allows us to explore worlds, to discover wonders, to feel warmth and inspiration. Light allows us to go further than we ever imagined possible.

We each have the power to radiate positivity, to cast inspiration, and to ignite and illuminate meaningful change. The world is as bright as you make it.



> DISCOVER MOR





CONTENT

3 CONTENT



4-9 NEW PRODUCTS

- 6 HF8R Core RGB NEW
- 8 P9R Core LEP NEW

10-23 FLASHLIGHTS

- 12 P2R Core
- 12 P3 Core
- 13 **P4 Core**
- 13 P4R Core
- 14 **P5 Core**
- 14 P5R Core
- 15 **P6 Core**
- 15 P6R Core
- 16 **P7 Core**
- 17 **P7R Core**
- 17 P9R Core LEP NEW
- 17 **P17R Core**
- 18 P6R Core QC
- 22 P6R Signature
- 22 P7R Signature
- 23 P18R Signature

24-27 KEYRING LAMPS



- 26 K4R
- 27 **K6R**
- 27 K6R Safety

28-33 KIDSLIGHTS



- 31 KIDLED2
- 31 KIDLED4R
- 32 KIDBEAM4
- 32 KIDCAMP6



34-39 XP-SERIES / X-SERIES

RETURN TO THE

CONTENTS FROM ANY PAGE

- 36 **XP30R**
- 39 **X21R**





40-55 HEADLAMPS

- 44 HF4R Core
 - 45 HF6R Core
 - 45 HF8R Core
 - 45 HF8R Core RGB NEW



- 48 **H5 Core**
- 48 H5R Core
- 49 H7R Core
- 49 H15R Core 49 **H19R Core**



- 50 H19R Signature
- 54 **NEO1R**
- 55 **NEO3**
- 55 **NEO5R**
- 55 **NEO9R**

56-57 CLIPLIGHT



58-63 LANTERNS

- 62 **ML4**
- 62 ML4 Warm Light
- 63 **ML6**
- 63 ML6 Warm Light
- 63 ML6 Connect WL

64-69 PORTABLE ENERGY



- 66 FLEX10
- 68 **FLEX3**
- 68 **FLEX7**
- 70-73 ACCESSORIES
- 76-79 TECHNOLOGIES
- **80-81 ABOUT US**
- **82-83** WARRANTY + ISO
- 84-85 NOTES + CONTACT

NEW PRODUCTS



HF8R CORE RGB

ADAPTIVE POWERHOUSE FOR HUNTING AND FISHING

The HF8R Core RGB is ideal for hunters and anglers. Its innovative Adaptive Light Beam Technology allows automatic dimming and focusing so you can be totally hands-free. Depending on your use case, you can choose between an additional red, green or blue front light.





02

04

07



06



PRESERVES NIGHT VISION - IDEAL FOR PREPARING YOUR GEAR AT NIGHT



GREEN ALMOST INVISIBLE TO SOME ANIMALS – SUITABLE FOR WILDLIFE WATCHING



BLUE CAN MAKE LIQUIDS MORE VISIBLE – HELPFUL WHEN TRACKING PREY



TRULY HANDS-FREE DIMS AND FOCUSES AUTOMATICALLY







- 01 Powerful headlamp with RGB front light
- 02 Automatic dimming and focusing thanks to our Adaptive Light Beam Technology – the system detects reflections and lighting conditions and automatically controls all light sources separately. This allows the HF8R to be used completely hands-free.
- **03 Powerful battery** can easily be recharged via Magnetic Charge System
- 04 Water and dustproof (IP68)
- 05 Lamp head tilts steplessly
- **06** Perfect light pattern for any range and virtually seamless focusing thanks to our **Digital Advanced Focus System**; optional manual operation via **Focus Wheel**
- **07** High-quality **aluminum housing**
- 08 Remote control and personalization via Ledlenser Connect App
- **09 Camouflage headband** with detachable overhead strap

More information on page 47



POR CORE LEP & NEW

True laser power in your hands! There is no need to decide between a highly focused white light with an extreme beam range or a homogeneous illumination at close range. Our new P9R Core LEP offers both and is ideal for search and rescue teams, members of the maritime sector as well as hunters and anglers.


LED BECOMES LEP LASER EXCITED PHOSPHOR TECHNOLOGY

Laser as a light source: Instead of using an LED, blue laser light is directed at a phosphor-coated plate and transformed into white light which then travels through two lenses, resulting in a white light that is highly focused and has an extreme range.

MAXIMUM BEAM RANGE:









- 01 Laser Excited Phosphor Technology creates a highly focused white light with an extreme beam range
- **02** White and red light for homogeneous illumination at close range
- **03 Intuitive mode switch** for direct access to light functions
- **04 Hard-anodized housing material** for added protection against wear and corrosion, high dust and water protection (IP68)
- **05** Convenient charging of the battery via **Magnetic Charge System**

More information on page 17



FLASHLIGHTS









— P-SERIES CORE





	I ZIN COINE	I J COILL
LED		
	1x Power LED	1x Power LED
ull Light Functions	Power / Mid Power / Low Power	Power / Mid Power / Low Power
-\(\sum_{-}\)- Luminous Flux¹ (lm)	120 / 50 / 15	90 / 50 / 15
□→ Beam Distance¹ (m)	65 / 45 / 15	110 / 70 / 40
© Run Time¹ (h)	0.5 / 1 / 5	3 / 4 / 6
Color Temperature (K)	6000 - 7500	6000 - 7500
(R) Color Rendering Index (CRI)	70	70
BATTERY AND CASE		
Battery	1x Li-ion Battery 3.7V mit Micro-USB	1x Micro (AAA) Alkaline 1.5V
Battery Capacity² (Wh / mAh)	0.74 / 200	
○ IP Level	IP54	IP54
Rechargeable	Yes	No
Charging Time ⁵ (min)	150	
<u>↓</u> Drop Height (m)	2	2
SIZE AND WEIGHT		
∠ Length – Defocused (mm)	103	96
Head Diameter (mm)	15	20
(g / oz) Weight incl. Battery (g / oz)	36 / 1.3	42 / 1.5
TECHNOLOGIE		
Smart Light Technology		
Flex Sealing Technology		
Magnetic Charge System		
Temperature Control		
Advanced Focus System	•	•
More Features	Energy Saving	Rapid Focus
PACKAGING		
Item no. Box / GTIN	502176 / 4058205020367	502597 / 4058205028462
Content Box	1 Battery Set, Pocket Clip, Micro-USB Charging Cable	1 Battery Set, Pocket Clip
OPTIONAL ACCESSORIES		
	502248 Lamp Adapter Type A	0337 Pouch Type D
	0337 Pouch Type D	502248 Lamp Adapter Type A
Further accessories on page 70	0380 USB Car Charger	
· · · · · · · · · · · · · · · · · · ·	· · · · · · · · · · · · · · · · · · ·	

P4 CORE X Power LED	D. Ballow View	DAD CODE
Power / Mid Power / Low Power 120 / 60 / 15 200 / 90 / 15 90 / 55 / 25 90 / 60 / 15 5 / 9 / 20 1.5 / 3 / 25 6000 - 7500 70 70 2x Micro (AAA) Alkaline 1.5V 1x Li-ion Battery Pack 3.7V 2.22 / 600 IP54 IP54 No Yes 150 2 2 146 155 15 58 / 2.0 55 / 1.9 Energy Saving Energy Saving 1 Battery Set, Pocket Clip Micro-USB Charging Cable 502248 Lamp Adapter Type A 0380 USB Car Charger	P4 CORE	P4R CORE
Power / Mid Power / Low Power 120 / 60 / 15 200 / 90 / 15 90 / 55 / 25 90 / 60 / 15 5 / 9 / 20 1.5 / 3 / 25 6000 - 7500 70 70 2x Micro (AAA) Alkaline 1.5V 1x Li-ion Battery Pack 3.7V 2.22 / 600 IP54 IP54 No Yes 150 2 2 146 155 15 58 / 2.0 55 / 1.9 Energy Saving Energy Saving 1 Battery Set, Pocket Clip Micro-USB Charging Cable 502248 Lamp Adapter Type A 0380 USB Car Charger		
120 / 60 / 15	1x Power LED	1x Power LED
90 / 55 / 25	Power / Mid Power / Low Power	Power / Mid Power / Low Power
5 / 9 / 20 6000 - 7500 6000 - 7500 70 70 2x Micro (AAA) Alkaline 1.5V 1x Li-ion Battery Pack 3.7V 2.22 / 600 IP54 No Yes 150 2 2 146 150 15 15 58 / 2.0 55 / 1.9 Energy Saving Energy Saving 1 Battery Set, Pocket Clip Micro-USB Charging Cable 502248 Lamp Adapter Type A 0380 USB Car Charger	120 / 60 / 15	200 / 90 / 15
6000 - 7500 70 70 70 2x Micro (AAA) Alkaline 1.5V 1x Li-ion Battery Pack 3.7V 2.22 / 600 IP54 No Yes 150 2 2 146 155 15 58 / 2.0 55 / 1.9 Energy Saving Energy Saving 1 Battery Set, Pocket Clip Micro-USB Charging Cable 502248 Lamp Adapter Type A 0380 USB Car Charger	90 / 55 / 25	90 / 60 / 15
70 2x Micro (AAA) Alkaline 1.5V 1x Li-ion Battery Pack 3.7V 2.22 / 600 IP54 No Yes 150 2 2 146 150 15 55 / 1.9 Energy Saving 502598 / 4058205028493 1 Battery Set, Pocket Clip Micro-USB Charging Cable 502248 Lamp Adapter Type A 0380 USB Car Charger	5 / 9 / 20	1.5 / 3 / 25
2x Micro (AAA) Alkaline 1.5V 1x Li-ion Battery Pack 3.7V 2.22 / 600 IP54 No Yes 150 2 2 146 15	6000 - 7500	6000 - 7500
2.22 / 600 IP54 No IP54 No Yes 150 2 2 146 150 15 15 58 / 2.0 55 / 1.9 Energy Saving Energy Saving 502598 / 4058205028493 1 Battery Set, Pocket Clip, Micro-USB Charging Cable 502248 Lamp Adapter Type A 0380 USB Car Charger	70	70
2.22 / 600 IP54 No IP54 No Yes 150 2 2 146 150 15 15 58 / 2.0 55 / 1.9 Energy Saving Energy Saving 502598 / 4058205028493 1 Battery Set, Pocket Clip, Micro-USB Charging Cable 502248 Lamp Adapter Type A 0380 USB Car Charger		
2.22 / 600 IP54 No Yes 150 2 2 146 155 15 58 / 2.0 Energy Saving Energy Saving 502598 / 4058205028493 1 Battery Set, Pocket Clip Micro-USB Charging Cable 502248 Lamp Adapter Type A 0380 USB Car Charger	2x Micro (AAA) Alkaline 1.5V	1x Li-ion Battery Pack 3.7V
No Yes 150 2 2 2 146 150 15 15 15 15 15 15 15 15 15 15 15 15 15 1.9 1 10 10		2.22 / 600
150 2 2 146 150 15 15 15 58 / 2.0 55 / 1.9 Energy Saving 502598 / 4058205028493 1 Battery Set, Pocket Clip Micro-USB Charging Cable 502248 Lamp Adapter Type A 0380 USB Car Charger	IP54	IP54
2 146 150 15 58 / 2.0 Energy Saving Energy Saving 502598 / 4058205028493 1 Battery Set, Pocket Clip Micro-USB Charging Cable 502248 Lamp Adapter Type A 0380 USB Car Charger	No	Yes
146		150
15 58 / 2.0 55 / 1.9 Energy Saving 502598 / 4058205028493 1 Battery Set, Pocket Clip Micro-USB Charging Cable 502248 Lamp Adapter Type A 0380 USB Car Charger	2	2
15 58 / 2.0 55 / 1.9 Energy Saving 502598 / 4058205028493 1 Battery Set, Pocket Clip Micro-USB Charging Cable 502248 Lamp Adapter Type A 0380 USB Car Charger		
55 / 1.9 Energy Saving 502598 / 4058205028493 1 Battery Set, Pocket Clip 1 Battery Set, Pocket Clip, Micro-USB Charging Cable 502248 Lamp Adapter Type A 0380 USB Car Charger	146	150
Energy Saving 502598 / 4058205028493 1 Battery Set, Pocket Clip Micro-USB Charging Cable 502248 Lamp Adapter Type A 0380 USB Car Charger	15	 15
502598 / 4058205028493 1 Battery Set, Pocket Clip 1 Battery Set, Pocket Clip, Micro-USB Charging Cable 502248 Lamp Adapter Type A 0380 USB Car Charger	58 / 2.0	 55 / 1.9
502598 / 4058205028493 1 Battery Set, Pocket Clip 1 Battery Set, Pocket Clip, Micro-USB Charging Cable 502248 Lamp Adapter Type A 0380 USB Car Charger		
502598 / 4058205028493 1 Battery Set, Pocket Clip 1 Battery Set, Pocket Clip, Micro-USB Charging Cable 502248 Lamp Adapter Type A 0380 USB Car Charger		
502598 / 4058205028493 1 Battery Set, Pocket Clip 1 Battery Set, Pocket Clip, Micro-USB Charging Cable 502248 Lamp Adapter Type A 0380 USB Car Charger		
502598 / 4058205028493 1 Battery Set, Pocket Clip 1 Battery Set, Pocket Clip, Micro-USB Charging Cable 502248 Lamp Adapter Type A 0380 USB Car Charger		
502598 / 4058205028493 1 Battery Set, Pocket Clip 1 Battery Set, Pocket Clip, Micro-USB Charging Cable 502248 Lamp Adapter Type A 0380 USB Car Charger		
502598 / 4058205028493 1 Battery Set, Pocket Clip 1 Battery Set, Pocket Clip, Micro-USB Charging Cable 502248 Lamp Adapter Type A 0380 USB Car Charger		
502598 / 4058205028493 1 Battery Set, Pocket Clip 1 Battery Set, Pocket Clip, Micro-USB Charging Cable 502248 Lamp Adapter Type A 0380 USB Car Charger		Energy Saving
1 Battery Set, Pocket Clip 1 Battery Set, Pocket Clip, Micro-USB Charging Cable 502248 Lamp Adapter Type A 0380 USB Car Charger		Lifely Saving
1 Battery Set, Pocket Clip 1 Battery Set, Pocket Clip, Micro-USB Charging Cable 502248 Lamp Adapter Type A 0380 USB Car Charger	E00E00 / /0E00E000 / 00	F004FF / /0500500000
Micro-USB Charging Cable 502248 Lamp Adapter Type A 0380 USB Car Charger	502598 / 4058205028493	
0380 USB Car Charger	1 Battery Set, Pocket Clip	
0380 USB Car Charger	E022/01 amp Adapter Type A	E022/9 Lamp Adapter Type A
		502271 USB Adapter



—P-SERIES CORE







reddot winner 2021







reddot winner 2021





502248 Lamp Adapter Type B 502259 Charging Station Type A



P5 CORE	P5R COR
---------	---------

	.ED		
\Box	LED Configuration	1x High Power LED	1x High Power LED
all	Light Functions	Power / Mid Power / Low Power	Boost / Power / Mid Power / Low Power (+ Position, Blink, S.O.S., Strobe)
<u>-\̈́\</u> -	Luminous Flux¹ (lm)	150 / 60 / 15	500 / 350 / 130 / 15
	Beam Distance¹ (m)	90 / 60 / 30	250 / 180 / 110 / 40
<u>(L)</u>	Run Time ¹ (h)	2.5 / 5 / 12	- / 1 / 3.5 / 25
₽ _K	Color Temperature (K)	6000 - 7500	6000 - 7500
(CRI)	Color Rendering Index (CRI)	70	70
	BATTERY AND CASE		
	Battery	1x Mignon (AA) Alkaline 1.5V	1x 14500 Li-ion Battery 3.7V
III > I	Battery Capacity² (Wh / mAh)		2.77 / 750
රු	IP Level	IP44	IP68
٩	Rechargeable	No	Yes
đ	Charging Time ⁵ (min)		120
<u>↓</u>	Drop Height (m)	2	2
S	SIZE AND WEIGHT		
7	Length - Defocused (mm)	120	123
\bigcirc	Head Diameter (mm)	26	29
ğ	Weight incl. battery (g / oz)	83 / 2.9	106 / 3.7
Ī	ECHNOLOGY		
(11)	Smart Light Technology	•	•
	Flex Sealing Technology		•
<u></u>	Magnetic Charge System		•
	Temperature Control		•
	Advanced Focus System	•	•
	More Features	Dual Power Source, Rapid Focus	Dimmable, Transportation Lock, Flicker-free, Memory Mode, Backup Mode, Emergency Light, Battery Indicator, Charge Indicator, Low Battery Warning
	PACKAGING		
	Item no. Box / GTIN	502599 / 4058205028523	502178 / 4058205020428
	Content Box	1 Battery Set, Lanyard	1 Battery Set, Lanyard, Magnetic Charging Cable

502700 Lamp Adapter Type F

0337 Pouch Type D



1x High Power LED	1x Xtreme LED
Power / Low Power	Boost / Power / Mid Power / Low Power (+ Position, Blink, S.O.S., Strobe)
300 / 25	900 / 600 / 240 / 15
200 / 60	240 / 190 / 120 / 25
3.5 / 25	- / 2 / 6 / 95
6000 - 7500	6000 - 7500
70	65
3x Micro (AAA) Alkaline 1.5V	1x18650 Li-ion Battery 3.7V
	9.25 / 2500
IP54	IP68
No	Yes
	300
2	2
117	151
32	35
130 / 4.6	170 / 6.0
	•
	•
	•
	•
•	•
Energy Saving, Rapid Focus	Dimmable, Transportation Lock, Flicker-free, Memory Mode, Backup Mode, Emergency Light, Temperature Control System, Battery Indicator, Charge Indicator, Low Battery Warning
502600 / 4058205028554	502179 / 4058205020459
1 Battery Set, Lanyard	1 Battery Set, Lanyard, Magnetic Charging Cable
	502250 Lamp Adapter Type C

1-9 Information on page 84



- 01 Extreme dust and water predection (IP68)
- 02 Advanced Focus System - stepless focusing
- 03 Flex Sealing Technology – can be used for a short time underwater (including the focusing system) to a depth of one meter
- **04** Personalize the light functions via **Smart Light Technology**
- **05** Convenient and safe charging the battery thanks to the Magnetic Charge System
- 06 Constant Light constant luminous flux over a long period
- **07 Flicker-free** constant light enables optimal and safe illumination



OPTIONAL ACCESSORIES

Further accessories on page 70

— P-SERIES CORE



P7 CORE

LED	
△ LED Configuration	1x Power LED
때 Light Functions	Power / Mid Power / Low Power
-\(\hat{\tau}\)- Luminous Flux¹ (lm)	450 / 250 / 40
⊏3→ Beam Distance¹ (m)	300 / 220 / 100
© Run Time ¹ (h)	1 / 2 / 25
Color Temperature (K)	6000 - 7500
© Color Rendering Index (CRI)	70
BATTERY AND CASE	
■ Battery	4x Micro (AAA) Alkaline 1.5V
Battery Capacity ² (Wh / mAh)	
□ IP Level	IP54
Rechargeable	No
Ō Charging Time⁵ (min)	
Drop Height (m)	1
SIZE AND WEIGHT	
∠ ⁷ Length – Defocused (mm)	130
Head Diameter (mm)	37
Ø Weight incl. Battery (g / oz)	175 / 6.2
TECHNOLOGY	
Smart Light Technology	
Flex Sealing Technology	
Magnetic Charge System	
Multi Core Optics	
Advanced Focus System	•
More Features	Energy Saving, Rapid Focus

PACKAGING	
Item no. Box / GTIN	502180 / 4058205020480
Content Box	1 Battery Set, Lanyard
OPTIONAL ACCESSORIES	
Further accessories on page 70	



P7R CORE

Magnetic Charging Cable

502251 Lamp Adapter Type D













1x Xtreme LED	1x Laser diode (LEP),1x COB LED (white light)	1x Xtreme LED
Boost / Power / Mid Power / Low Power (+ Position, Blink, S.O.S., Strobe)	Boost / Power / Mid Power / Low Power	Boost / Power / Mid Power / Low Power (+ Position, Blink, S.O.S., Strobe)
1400 / 1000 / 440 / 15	LEP: 400 / 250 / - / 75 COB: 1000 / 550 / 300 / 150	1200 / 900 / 350 / 15
300 / 210 / 130 / 15	LEP: 1300 / 1000 / - / 550 COB: 40 / 30 / 20 / 15	560 / 420 / 270 / 50
- / 2 / 4 / 90	LEP: - / 4 / - / 10 COB: - / 4 / 8 / 20	- / 2.75 / 12 / 200
6000 - 7500	LEP: 6000 - 8000 COB: 5700-6700	6000 - 7500
70	LEP: 65 COB: 80	65
1x 21700 Li-ion Battery 3.7V	1x 21700 Li-ion Battery 3.7V	1x LiFePO4 Battery pack 6.4V
17.76 / 4800	17.76 / 4800	36.48 / 5700
IP68	IP68	IP54
Yes	Yes	Yes
270	270	270
2	2	1
158	176	290
35	41	53
202 / 7.1	269 / 9.49	715 / 25.2
•	•	•
•		
•	•	•
•		
•		•
Dimmable, Transportation Lock, Flicker-free, Memory Mode, Backup Mode, Emergency Light, Temperature Control System, Battery Indicator, Charge Indicator, Low Battery Warning	Laser Excited Phosphor Technology, Temperature Control , Mode Switch, Magnetic Charge System, Dimmable , Red Light, Transportation Lock, Flicker Free, Backup Mode	
502181 / 4058205020510	502987 / 4058205034647	502182 / 4058205020541
1 Battery Set, Lanyard,	1 Battery Set, Lanyard, Pouch,	1 Set of Batteries, Intelligent Clip,

502251 Lamp Adapter Type D

Magnetic Charging Cable



Wall Mount, Power Adapter,

Magnetic Charging Cable

0042 Signal Cone 53 mm

P6R CORE QC



- 01 Equipped with a


 Multicolor LED with white,
 red, green and blue light
- **02 Multicolor Strobe** colored flashes of light with irritating glare effect for emergencies
- **03 Easy Operation** the rotary switch enables quick color changes
- **04 Advanced Focus System –** stepless focusing



P6R CORE QC



		P6R CORE QC
L	.ED	
\cap	LED Configuration	1x Power LED
иЩ	Light Functions (weißes Licht)	Power / Mid Power / Low Power
<u>-\\\</u>	Luminous Flux¹ (lm)	270 / 120 / 15
∺	→ Beam Distance¹ (m)	335 / 220 / 80
<u>(L)</u>	Run Time ¹ (h)	5 / 14 / 110
§ K	Color Temperature (K)	6000 - 6500
(RI)	Color Rendering Index (CRI)	80 (white light)
E	BATTERY AND CASE	
	Battery	1x Li-ion Battery 3.7V
III-	Battery Capacity² (Wh / mAh)	9.25 / 2500
<u>ထ</u>	IP Level	IP54
Φ	Rechargeable	Yes
<u></u>	Charging Time ⁵ (min)	300
<u>^</u>	Drop Height (m)	1.5
S	SIZE AND WEIGHT	
<u> </u>	Length – Defocused (mm)	157
0	Head Diameter (mm)	42
<u> </u>	Weight incl. Battery (g / oz)	207 / 7.3
Т	ECHNOLOGY	
()	Rapid Focus	•
	Advanced Focus System	•
	More Features	Multicolor Strobe, Singlecolor Strobe
P	PACKAGING	
	Item no. Box / GTIN	502517 / 4058205026819
	Content Box	1 Battery Set, Lanyard, Micro-USB Charging Cable
C	PTIONAL ACCESSORIES	
		502251 Lamp Adapter Type D
Fui	rther accessories on page 70	502729 Remote Switch Type G



P7R SIGNATURE & Control of the second second

PREMIUM ILLUMINATION


















- **03** Additional **red secondary light** on the side of the housing, e. g. to maintain the night vision
- **04 Hard-anodized housing material** for additional protection against wear and corrosion
- 05 Extreme dust and water protection (IP68)
- **06 Flex Sealing Technology** can be used for a short time underwater (including the focusing system) to a depth of one meter
- **07** Personalize the light functions thanks to **Smart Light Technology**
- 08 Constant Light consistent level of brightness over time
- 09 Integrated battery and charge status indicator







-**>** 2000 lm¹ — 330 m¹ —



90 h¹

MAXIMUM PERFORMANCE, STYLISH DESIGN













P6R SIGNATURE

P7R SIGNATURE

L	ED		
\bigcirc	LED Configuration	1x Xtreme LED, (1x red LED)	1x Xtreme LED, (1x red LED)
all	Light Functions	Boost / Power / Mid Power / Low Power (+ Position, Blink, S.O.S., Strobe, Red Light)	Boost / Power / Mid Power / Low Power (+ Position, Blink, S.O.S., Strobe, Red Light)
-\\\\-	Luminous Flux¹ (lm)	1400 / 1100 / 450 / 15	2000 / 1200 / 500 / 15
⇔	Beam Distance ¹ (m)	240 / 190 / 110 / 20	330 / 200 / 130 / 20
<u>(L)</u>	Run Time ¹ (h)	- / 1.25 / 2.5 / 60	- / 2 / 3.25 / 90
_¶ĸ	Color Temperature (K)	6000 - 7500	6000 - 7500
(RI)	Color Rendering Index (CRI)	80	80
В	ATTERY AND CASE		
·	Battery	1x 18650 Li-ion Battery 3.6V	1x 21700 Li-ion Battery 3.7V
III.	Battery Capacity² (Wh / mAh)	10.89 / 3000	17.76 / 4800
ල	IP Level	IP68	IP68
٩	Rechargeable	Yes	Yes
đ	Charging Time ⁵ (min)	225	270
<u></u>	Drop Height (m)	2	2
S	IZE AND WEIGHT		
7	Length – Defocused (mm)	151	158
\bigcirc	Head Diameter (mm)	35	35
(g)	Weight incl. Battery (g / oz)	170 / 6.0	202 / 7.1
T	ECHNOLOGY		
1	Smart Light Technology	•	•
	Flex Sealing Technology	•	•
<u></u>	Magnetic Charge System	•	•
	Multi-Core Optics	•	•
	Advanced Focus System	•	•
	More Features	Red Alternate Light, Mode Switch, Emergency Light, Temperature Control, Dimmable, Transportation Lock, Flicker- free, Memory Function, Backup Mode, Emergency Light, Battery Indicator, Char- ge Indicator, Low Battery Warning	Red Alternate Light, Mode Switch, Emergency Light, Temperature Control, Dimmable, Transportation Lock, Flicker- free, Memory Function, Backup Mode, Emergency Light, Battery Indicator, Charge Indicator, Low Battery Warning
Р	ACKAGING		
	Item no. Box / GTIN	502189 / 4058205020756	502190 / 4058205020787
	Content Box	1 Set of Batteries, Leather Belt Pouch, Lanyard, Magnetic Charging Cable, Pocket Clip, USB Power Adapter, Wall Bracket	1 Set of Batteries, Leather Belt Pouch, Lanyard, Magnetic Charging Cable, Pocket Clip, USB Power Adapter, Wall Bracket



P18R SIGNATURE

3x Xtreme LED

Boost / Power / Mid Power / Low Power (+ Position, Blink, S.O.S., Strobe)

4500 / 2600 / 1000 / 30

720 / 420 / 260 / 50

- / 2.5 / 4.5 / 70

6000 - 7200

70

1x Li-ion Battery Pack 11.1V
33.3 / 3000
IP54
Yes
330

171

86

637 / 22.5

_

X-Lens Technology, Rapid Focus, Dimmable, Transportation Lock, Flicker-free, Memory Function, Backup Mode, Emergency Light, Battery Indicator, Charge Indicator, Low Battery Warning

502191 / 4058205020817

1Set of Batteries, Lanyard, USB Power Adapter, Magnetic Charging Cable

P-SERIES SIGNATURE





KEY RING LIGHTS

















1/	,	
Κ	4	к

		K4R	
L	ED		
$\overline{\triangle}$	LED Configuration	1x Power LED	
иЩ	Light Functions	Boost / Power / Low Power	
- <u>`</u> Ċ;-	Luminous Flux¹ (lm)	120 / 80 / 20	
□ ;	Beam Distance ¹ (m)	30 / 25 / 10	
<u>(L)</u>	Run Time ¹ (h)	- / 1 / 3.5	
В	ATTERY AND CASE		
	Battery	1x Li-ion Battery 3.7V	
III-)	Battery Capacity ² (Wh / mAh)	0.67 / 180	
٩	Rechargeable	Yes	
Ø	Charging Time ⁵ (min)	180	
ආ	IP Level	IP2X	
S	IZE AND WEIGHT		
7	Length (mm)	52	
\bigcirc	Width (mm)	25	
g	Weight incl. Battery (g / oz)	20 / 0.7	
F	EATURES		
		Transportation Lock, Battery Indicator, Charge Indicator	
Р	ACKAGING		
	Item no. Box / Gray	Gray: 502574 / 4058205029117	
	Item no. Box / Rosé-Gold	Rose Gold: 502575 / 4058205029148	
	Content Box	Carabiner, Key Ring	










Carabiner, Key Ring

Carabiner, Key Ring, Wrist Strap

K6R	K6R Safety
1x High Power LED	1x High Power LED
Boost / Power / Low Power (+ red light)	Boost / Power / Low Power (+ Strobe)
400 / 200 / 20	400 / 200 / 20
80 / 50 / 15	80 / 50 / 15
- / 1.5 / 10	- / 1.5 / 8
1x Li-ion Battery 3.7V	1x Li-ion Battery 3.7V
2 / 550	1.48 / 400
Yes	Yes
180	180
IP2X	IP2X
62	66
30	30
30 / 1.1	32 / 1.1
Transportation Lock, Red Light, Battery Indicator, Charge Indicator	Transportation Lock, Shrill Alarm, Battery Indicator, Charge Indicator
Gray: 502577 / 4058205028318	Safety Gray: 502580 / 4058205028370
Rose Gold: 502578 / 4058205028622	Rose Gold: 502581 / 4058205028721

KIDSLIGHTS









KIDS LIGHTS LIGHT, FUN AND SAFETY

The Ledlenser KidsLights series lights specifically address the needs and requirements of children. They offer a wide range of uses, from the selfmade cave to the safe way to school, a multitude of colorful light functions, quick and easy operation, and practical energy-saving features. And, most importantly, safety always comes first. For instance, glaring effects and the luminous flux are reduced and all headlamps come with safety headbands which open automatically.



Versatile: white light, red light and blue light with optional flashing functions (red and blue)

Clever: Optics with reduced glaring for children's sensitive eyes

Energy-saving: automatic switch-off after 20 minutes (optional)



Practical: integrated metal clip for further attachment options without headband (e.g. on school satchel, backpack, clothing)



Safe: Pressure sensitive headband that releases automatically to prevent accidental injury





















		_
LED		
△ LED Configuration	1x Power LED (White), 1x LED (Red), 1x LED (Blue)	1x Power LED (White), 1x LED (Red), 1x LED (Blue)
ull Light Functions	Power (White), Low Power (White), (Power (Red), Blink (Red), Power (Blue), Blink (Blue), Blink (Red / Blue))	Power (White), Low Power (White), (Power (Red), Blink (Red), Power (Blue), Blink (Blue), Blink (Red / Blue))
-\(\hat{\tau}\)- Luminous Flux¹ (lm)	40 / 5	40 / 5
□→ Beam Distance¹(m)	9 / 2	9 / 2
Run Time ¹ (h)	1.5 / 20	2 / 18
BATTERY AND CASE		
■ Battery	1 x AAA Alkaline 1.5V	1 x Li-ion 3.7V (intern)
Battery Capacity ² (Wh / mAh)	-	1.036/280
Rechargeable	No	Yes
the Charging Time (min)		60
○ IP Level	IPX4	IP56
SIZE AND WEIGHT		
O Durchmesser (mm)	54	37
Weight incl. Battery (g / oz)	35 / 1.2	25 / 0.9
FEATURES		
	White Light, Red Light, Blue Light, Automatic Switch-Off (optional), Safety Headband, Metal Clip for Mounting as Clip Light	White Light, Red Light, Blue Light, Automatic Switch-Off (optional), Safety Headband, Metal Clip for Mounting as Clip Light, Charge Indicator
PACKAGING (BOX)		
Item no. / GTIN	502537 (Green) / 4058205027038	502535 (Green) / 4058205026970
Item no. / GTIN	502538 (Purple) / 4058205027069	502536 (Purple) / 4058205027007
Content Box	1 Set of Batteries	Micro-USB Charging Cable

^{*} Caution: Not suitable for children under 36 months.

1-9 Information on page 84



KIDSLIGHTS





KIDBEAM4*


KIDCAMP6*

LED		
△ LED Configuration	1x Power LED (White), 1x LED (Red), 1x LED (Blue), 1x LED (Green)	1x Power LED (White), 1x LED (Red), 1x LED (Blue), 1x LED (Green)
─────────────────────────────────────	Power (White) / Low Power (White) (+ Power (Red), Power (Blue), Power (Green), Blink (Red und Blue))	Power (White) / Low Power (White) (+ Power (Red), Power (Blue), Power (Green), Blink (Red, Blue und Green))
-\(\hat{\chi}\)- Luminous Flux¹ (lm)	70 / 10	60 / 10
⊏ ⇒ Beam Distance¹ (m)	12 / 5	- / -
L Run Time ¹ (h)	4 / 18	8 / 40
BATTERY AND CASE		
- 	2 x AAA Alkaline 1.5V	3 x AAA Alkaline 1.5V
Battery Capacity² (Wh / mAh)	-	-
	No	No
ि Charging Time⁵ (min)	_	-
P IP Level	IP44	IP44
SIZE AND WEIGHT		
O Durchmesser (mm)	35	75
Weight incl. Battery (g / oz)	72 / 2.5	95 / 3.4
FEATURES		
	White Light, Red Light, Blue Light, Green Light, Automatic Switch-Off (optional), Clip	White Light, Red Light, Blue Light, Green Light, Automatic Switch-Off (optional), Fold-Out Hook for Hanging Up the Light
PACKAGING (BOX)		
Item no. / GTIN	502754 (Green) / 4058205030861	502753 (Green) / 4058205030847
Item no. / GTIN	502789 (Purple) / 4058205031653	502786 (Purple) / 4058205031561
Content Box	1 set of batteries	1 set of batteries

^{*} Caution: Not suitable for children under 36 months. Caution: Use under direct adult supervision.

1-9 Information on page 84







KIDBEAM4 AAA Alkaline Batteries











Exploring with your first own flashlight:

The robust Kidbeam4 lights up in four different colors and impresses with practical, child-specific features such as the integrated clip or the automatic switch-off function.

KIDCAMP6 AAA Alkaline Batteries















For cozy evenings of playing or reading:


The Kidcamp6 provides the right mood and lights up in four different colors. It can be mounted in various ways thanks to the foldout hook, e. g. in a tent or caravan.



XP-SERIES / X-SERIES: LIGHT FOR EXTREME NEEDS LEDLENSER



ULTIMATE LIGHT PERFORMANCE





- **01 High-end portable searchlight** with up to 32,000 lumens¹
- **02** Extreme Search Beam 30 powerful automotive LEDs combined with unique optics for extreme long-range vision without glare at close range
- **03** Active Cooling Technology powerful fan for maximum light output over a long period of time
- **04 AMPShare powered by Bosch battery** with fast charging function
- 05 Compact dimensions and perfect weight distribution for optimal handling and single-handed operation
- **06** Remote control with up to 200 m range
- **07** Extremely robust due to protective elements and robust front glass
- 08 Screw thread for tripod mounting
- **09 Made in Germany** development and production in Germany according to highest quality standards



— X 2 1 P and a specific control of the state of the stat



- **01 Extreme light output** up to 800 meters¹ beam distance with up to 5000 lumens¹ thanks to seven Xtreme LEDs
- **02 X-Lens Technology** precise synchronization of the bundles of rays from several reflector lenses to form an extremely homogeneous, stage-like floodlight or a very sharply focused high beam
- **03 Advanced Focus System** stepless focusing
- **04** High-quality battery system **Safety Ytrion Cell** over 5000 charging cycles without significant loss of capacity
- **05** Quick to hand convenient charging with the **Floating Charge System**
- **06 Great ease of use** 7 light functions, 4 light programs, 2 energy modes, and 1 multi-function switch



EXTREME POWER

RECHARGEABLE & MULTIFUNCTIONAL

LED	
△ LED Configuration	7x Xtreme LED
Ⅲ Light Functions	Boost / Power / Low Power (+ Blink, S.O.S., Strobe, Position)
-\rac{1}{\sqrt{-}} Luminous Flux¹(lm)	5000 / 3500 / 200
□→ Beam Distance¹ (m)	800 / 700 / 150
L Run Time¹ (h)	- / 5 / 40
BATTERY AND CASE	
Battery	1x LiFePO4 Battery Pack 9.6V
Battery Capacity ² (Wh / mAh)	48 / 5000
Rechargeable	Yes
Ĉ Charging Time⁵ (min)	210
IP Level	IP54
SIZE AND WEIGHT	
✓ Length – defocused (mm)	405
Head diameter (mm)	95
(g / oz)	1315 / 45.9
TECHNOLOGY	
Smart Light Technology	•
Rapid Focus	•
Floating Charge System	•
Advanced Focus System	•
X-Lens Technology	•
Emergency Light	•
Safety Ytrion Cell	•
Temperature Control	•
More Features	Energy Saving, Constant Light, Charge Indicator, Battery Indicator, Dimmable, Transportation Lock
PACKAGING	
Item no. Carrying Case / GTIN	501967 / 4058205015394
Contents	1 Battery Set, Floating Charge System, Assembly Material, Power Supply Unit, Roll Protection, Tripod Holder, Carrying Strap, Case
OPTIONAL ACCESSORIES	
	0386 Car Charger









REVOLUTIONARY TECHNOLOGIES FOR MAXIMUM FLEXIBILITY:

With the HF8R, Ledlenser introduces its first hands-free headlamp. Why break your flow at work when your headlamp will adjust automatically or transition seamlessly, while providing you with the perfect light pattern. Without a battery box at the back of your head or an additional cable at the headband, you will be more comfortable and move more freely.





TRULY HANDS-FREE


DIMS AND FOCUSES

AUTOMATICALLY









- **01 Powerful headlamp** with additional red front light
- 02 Automatic dimming and focusing thanks to our v – the system detects reflections and lighting conditions and automatically controls all light sources separately. This allows the HF8R to be used completely hands-free.
- **03 Powerful battery** can easily be recharged via Magnetic Charge System
- **04** Water and dustproof (IP68)
- 05 Lamp head tilts steplessly
- **06** Perfect light pattern for any range and virtually seamless focusing thanks to our D optional manual operation via Focus Wheel
- **07** High-quality **aluminum housing**
- **08** Remote control via **Ledlenser Connect App** (upgrade with additional features available)





-HF-SERIES









	HF4R CORE
LED	
← LED Configuration	2x High Power LED, 1x Red LED
때 Light Functions	Boost / Power / Mid Power / Low Power (+ Red Light)
├- Luminous Flux¹(lm)	500 / 300 / 120 / 20
⇒ Beam Distance¹ (m)	130 / 100 / 60 / 15
D Run Time ¹ (h)	- / 2.5 / 5 / 35
Color Temperature (K)	5200 – 6200
R Color Rendering Index (CRI	70
BATTERY AND CASE	
■ Battery	1x Li-ion Battery Pack 3.7V
■ Battery Capacity² (Wh / mA	h) 3.7 / 1000
∩ IP Level	IP68
Rechargeable	Yes
Charging Time⁵ (min)	180
<u>↓</u> Drop Height(m)	2
WEIGHT	
o g\ Weight incl. Battery (g / oz)	72 / 2.54
TECHNOLOGIE	
Adaptive Light Beam	
Digital Advanced Focus Systo	em
Magnetic Charge System	•
Temperature Control Syste	m •
Cooling Technology	-
More Features	Fusion Beam, Transportation Lock, Memory Function, Backup Mode, Battery Indicator, Charge Indicator, Low Battery Warning
PACKAGING	
Item no. Box / GTIN	502790 Black / 4058205031684
Item no. Box / GTIN	502791 Blue / 4058205031707
Item no. Box / GTIN	502792 Red / 4058205031738
Content Box	Connect Adapter, Magnetic Charging Cable

(USB-C)

















HF8R CORE

HF8R CORE RGB



THI OIL COILE	THE CONE	THE CONE ROD
2x Xtreme LED, 1x High Power LED, 1x Red LED	3x Xtreme LED, 1x High Power LED, 1x Red LED	3x Xtreme LED, 1x High Power LED, 1x RGB LED
Boost / Power / Mid Power / Low Power (+ Red Light)	Boost / Power / Mid Power / Low Power (+ Red Light) (+S.O.S., Alpine distress signal via App)	Boost / Power / Mid Power / Low Power (+ RGB Light) (+S.O.S., Alpine distress signal via App)
800 / 500 / 250 / 20	1600 / 900 / 300 / 20	1600 / 900 / 300 / 20
160 / 140 / 80 / 25	210 / 200 / 100 / 25	210 / 200 / 100 / 25
-/3/6/60	- / 3.5 / 10 / 90	- / 3,5 / 10 / 90
5200 – 6200	5200 – 6200	5200 – 6200
70	70	70
1x Li-ion Battery Pack 3.7V	1x Li-ion Battery Pack 3.7V	1x Li-ion Battery Pack 3.7V
7.4 / 2000	13.7 / 3700	13.7 / 3700
IP68	IP68	IP68
Yes	Yes	Yes
225	270	270
2	2	2
126 / 4.44	194 / 6.84	194 / 6.84
	•	•
•	•	•
•	•	•
•	•	•
•	•	•
Memory Function, Transportation Lock, Backup Mode, Aluminum housing, Battery Indicator, Charge Indicator, Low Battery Warning	Bluetooth®, Transportation Lock, Memory Function, Backup Mode, Aluminum housing, Emergency Light, Battery Indicator, Charge Indicator, Low Battery Warning	RGB Light, Bluetooth®, Transportsicherung, Memory Function, Backup Mode, Aluminium- gehäuse, Emergency Light, Battery Indicator, Charge Indicator, Low Battery Warning, Dim- mable, Remote control and personalisation via Ledlenser Connect App
502796 Black / 4058205031837	502801 Black / 4058205031943	503089 Camouflage / 4058205036634
502966 Blue / 4058205034319		
502967 Red / 4058205034340		
502797 White / 4058205031851		
Comfort Pad, Connect Adapter, Magnetic Charging Cable (USB-C)	Comfort Pad, Connect Adapter, Magnetic Charging Cable (USB-C), removable Overhead Strap	Comfort Pad, Connect Adapter, Magnetic Charging Cable (USB-C), removable Overhead Strap

Optional accessories on page 72 1-9 Information on page 84















- **01** Intuitive operation and stepless dimming thanks to the wheel switch on the lamp head
- 02 Strong dust and water predection (IP67)
- 03 Stepless swivel mechanism for vertical alignment of the light cone
- **04 Advanced Focus System –** stepless focusing
- **05** Convenient and safe charging of the battery thanks to the **Magnetic Charge System**
- 06 Integrated battery and charge status indicator
- 07 Ledlenser Connecting System one interface for many accessories



->;-1000 lm¹ 250 m¹ ○ 65 h¹



—H-SERIES CORE





502256 Universal Mounting Bracket

H5 CORE H5R CORE

LED		
← LED Configuration	1x High Power LED	1x High Power LED
Ill Light Functions	Boost / Power / Low Power	Boost / Power / Low Power
-\hat\(\frac{1}{\chi}\)- Luminous Flux\(\text{1}\)(lm)	350 / 200 / 15	500 / 300 / 15
	160 / 120 / 30	200 / 150 / 30
Run Time¹ (h)	- / 2 / 20	- / 2 / 50
Color Temperature (K)	6000 - 7500	6000 - 7500
(R) Color Rendering Index (CRI)	70	70
BATTERY AND CASE		
	2x Mignon (AA) Alkaline 1.5V	1x Li-ion Battery Pack 3.7V
Battery Capacity² (Wh / mAh)	-	6.66 / 1800
∩ IP Level	IP67	IP67
Rechargeable	No	Yes
টি Charging Time⁵ (min)	-	210
<u>↓</u> Drop Height(m)	1.5	1.5
SIZE AND WEIGHT		
Head Diameter (mm)	32	32
Weight incl. Battery (g / oz)	178 / 6.3	167 / 5.9
TECHNOLOGY		
Multi-Core Optics		•
Flex Sealing Technology	•	•
Magnetic Charge System		•
Fusion Beam		
Advanced Focus System	•	•
More Features	Cooling Technology, Dimmable, Transportation Lock, Energy Saving	Cooling Technology, Temperature Control, Dimmable, Transportation Lock, Flicker-free, Memory Mode, Backup Mode, Battery Indica- tor, Charge Indicator, Low Battery Warning, Constant Light
PACKAGING		
Item no. Box / GTIN	502193 / 4058205020848	502121 / 4058205020879
Content Box	1 Set of Batteries	1 Set of Batteries, Magnetic Charging Cable
OPTIONAL ACCESSORIES		

502451 Transp. Silicone Headband










H19R CORE

H/R CURE	HISK CURE	HI9R CURE
1x Xtreme LED	1x Xtreme LED	2x Xtreme LED
Boost / Power / Low Power	Boost / Power / Low Power	Boost / Power / Mid Power / Low Power
1000 / 600 / 15	2500 / 1000 / 20	3500 / 1600 / 800 / 200
250 / 200 / 25	250 / 170 / 20	300 / 230 / 150 / 80
- / 4 / 65	- / 5 / 80	- / 4 / 7 / 20
6000 – 7500	6000 – 7500	6000 – 7500
70	70	70
1x 21700 Li-ion Battery 3.7V	1x Li-ion Battery Pack 7.4V	1x Li-ion Battery Pack 7.4V
17.76 / 4800	35.52 / 4800	35.52 / 4800
IP67	IP67	IP68
Yes	Yes	Yes
210	330	330
1.5	1.5	1.5
41	47	68
259 / 9.1	380 / 13.4	374 / 13.2
	•	•
•	•	-
•	•	•
		•
•	•	
Cooling Technology, Temperature Control, Dimmable, Transportation Lock, Flicker- free, Memory Mode, Backup Mode, Battery Indicator, Charge Indicator, Low Battery Warning, Constant Light	Cooling Technology, Temperature Control, Dimmable, Transportation Lock, Flicker- free, Memory Mode, Backup Mode, Battery Indicator, Charge Indicator, Low Battery Warning, Constant Light	Temperature Control, Cooling Technology, Optisense Technology, Dimmable, Trans- portation Lock, Flicker-free, Memory Mode, Backup Mode, Battery Indicator, Charge Indicator, Low Battery Warning, Constant Light, Red Light
502122 / 4058205020909	502123 / 4058205020930	502124 / 4058205020961
1 Set of Batteries, Magnetic Charging Cable	1 Set of Batteries, Magnetic Charging Cable	1 Set of Batteries, Magnetic Charging Cable
502262 21700 Li-lon Recharge. Battery	502253 Belt Clip Type A	502256 Universal Mounting Bracket
	- 002200 Dett clip Type A	- 002200 Offiver Sat Modifiling Dracket

502256 Universal Mounting Bracket 1-9 Information on page 84

Further accessories on page 72









- **01 Fusion Beam** individually adjustable flood and spotlight for a unique light image with perfect illumination
- **02 Multi-Core Optics** homogeneous light image thanks to special faceting of the lens
- **03 Ledlenser Connect App** and **Bluetooth® remote control** enable personalization and remote control of the light functions
- **04 Optisense Technology** automatic adaptation to the light conditions thanks to the integrated sensor
- **05** Extreme **Dust and Water Protection (IP68)**
- **06 Additional Red Light** to maintain night vision
- **07** Stepless **Swivel Mechanism** for vertical alignment of the light cone
- **08 Ledlenser Connecting System** one interface for many accessory parts
- 09 Additional Content
- 10 Reflective Headband






		TITE SIGNATURE
L	ED	
$\overline{\triangle}$	LED Configuration	2x Xtreme LED
वा॥	Light Functions	Boost / Power / Mid Power / Low Power (+ Strobe, Positon, SOS, Blink, Red Light)
<u>-\\\</u>	Luminous Flux¹ (lm)	4000 / 1800 / 800 / 200
⇔	Beam Distance ¹ (m)	330 / 250 / 150 / 80
<u>(L)</u>	Run Time ¹ (h)	_ / 3.5 / 7 / 20
- Ik	Color Temperature (K)	6500
(CRI)	Color Rendering Index (CRI)	80
В	ATTERY AND CASE	
	Battery	1x Li-ion Akkupack 7.4V
	Battery Capacity ² (Wh / mAh)	35.52 / 4800
ф —	IP Level	IP68
Φ	Rechargeable	Ja
đ	Charging Time ⁵ (min)	330
<u>↓</u>	Drop Height (m)	1.5
S	IZE AND WEIGHT	
0	Head Diameter (mm)	68
₫	Weight incl. Battery (g / oz)	374 / 13.2
Т	ECHNOLOGY	
O	Fusion Beam	•
<u></u>	Magnetic Charge System	•
	Temperature Control	•
	More Features	Mutli-Core Optics, Red Light, Optisense, Coolin Technology, Emergency Light, Bluetooth®8, Dimmable, Transportation Lock, Flicker-free, Memory Mode, Backup Mode, Battery Indicato Charge Indicator, Low Battery Warning, Constant Light
Р	ACKAGING	
	Item no. Box / GTIN	502198 / 4058205021111
	Content Soft Case	Bluetooth® remote control, 1 Set of Batteries, Helmet Clips, Adapter for GoPro, Helmet Holder, Hook-and-Loop straps, Ad esive Pads, Magnetic Charging Cable, Tripod Holder, USB Power Adapter, Universal Holder, Extension Cable, Adhesive Pads
0	PTIONAL ACCESSORIES	


More Accessories on page 74



¹⁻⁹ Information on page 84

502310 2x 21700 Li-lon Recharge. Battery











ULTRALIGHT AND VERSATILE



Additional red light as a signal light and to maintain charging via Magnetic night vision capability



Quick and easy battery Charge System with status LED



Tilting lamp head for individual adjustment of the light cone

BRIGHT ALLROUNDER FOR SPORTY MISSIONS



Perfect light pattern for fast-moving activities with combined close and long distance light



Tilting lamp head for light cone



Minimalist, ergonomic design individual adjustment of the with cable tunnel for perfect fit and wearing; 360° visibility thanks to red flashing rear light; easy operation with three AAA batteries

COMPACT POWER FOR AMBITIOUS ATHLETES



Perfect light pattern for fast-moving activities with combined close and long distance light



360° visibility thanks to red flashing rear light and reflective headband; quick and easy battery charging via Magnetic Charge System with status LED



Tilting lamp head for individual adjustment of

THE PERFECT LIGHT FOR TRAIL RUNNERS



Extremely powerful trail running headlamp with outstanding light image; multiple light sources perfectly illuminate near and far in every situation



Extremely powerful, replaceable battery pack; rechargeable via Magnetic Charge System with status LED



Ergonomic design with removable overhead strap for perfect fit and wearing comfort during outdoor activities: included chest belt as additional attachment option

¹⁻⁹ Information on page 84



-NEO-SERIES















NE01R

	NEO1R
LED	
△ LED Configuration	1x High Power LED
Ill Light Functions	Boost / Power / Low Power
-\rac{\'}{\'}- Luminous Flux¹ (lm)	250 / 150 / 20
□→ Beam Distance¹ (m)	80 / 50 / 15
L Run Time ¹ (h)	-/3/15
BATTERY AND CASE	
⊞ Battery	1x Li-ion Battery Pack 3.7 V
Battery Capacity ² (Wh / mAh)	2.7 / 730
Rechargeable	Yes
Ō Charging Time⁵ (min)	180
○ IP Level	IP67
SIZE AND WEIGHT	
Head Diameter (mm)	48
🖄 Weight incl. Battery (g / oz)	39 / 1.4
TECHNOLOGY	
Fusion Beam	
Magnetic Charge System	•
Temperature Control	•
More Features	Low Battery Warning, Battery Indicator, Charge Indicator, Red Light, Transportation Lock, Backup Mode
PACKAGING	
Item no. Box / GTIN	502713 Blue / 4058205029971
Item no. Box / GTIN	502720 White/Lime / 4058205030168
Item no. Box / GTIN	502712 Black / 4058205029957
Content Box	Magnetic Charging Cable
OPTIONAL ACCESSORIES	

0332 Pouch Type H

Further accessories on page 72







The CU2R can be easily used as a **BACKLIGHT FOR MANY** headlamps

for example HF-Series (p. 9) or NEO1R (p. 54)









LED 1x Power LED (White), △ LED Configuration 2x LED (Red) Power (White), Low Power (White), ■ Light Functions (+ Power (Red), Blink (White), Blink (Red)) -\(\)- Luminous Flux\(^1\) (lm) 40 / 5 0/2

□→ Beam Distance (m)	9 / 2
Run Time ¹ (h)	2 / 18
BATTERY AND CASE	
Battery	1 x Li-ion 3.7V (internal)
Battery Capacity² (Wh / mAh)	1036 / 280
(a) Rechargeable	Yes
ि Charging Time⁵ (min)	60
P Level	IPX4
CIZE AND WEIGHT	

25 / 0.9

S	IZE AND WEIGHT
0	Diameter (mm)

Weight incl. Battery (g / oz)

FEATURES


Additional White and Red Flashing Light, Metal Clip for Attachment as Clip Light, Transportation Lock, Wrist Strap

PACKAGING (BOX)	
Item no. / GTIN	502730 / 4058205030366
Content Box	Micro-USB Charging Cable, Wrist Strap

1-9 Information on page 84

CU2R is your trusted light partner that provides extra everyday safety in dim conditions and beyond - whether it's on a walk with the dog, on an evening run during rush hour or in everyday life as a rear light on clothing or backpack.

- 01 Compact, lightweight and versatile signal light with reflective wristband to increase safety in the dark
- 02 One white LED and two extra bright red LEDs offering two modes (power, blink)
- 03 Intuitive operation with two separate switches for white light and red light
- 04 Elastic strap with hook-and-loop closure and metal clip for quick and flexible attachment, e. g. on upper arm, clothing or backpack





OUTDOOR LANTERNS LEDLENSER

ML6 CONNECT WL se desple







750 lm¹ — 180 h¹ —







- 01 Micro Prism Technology patented4 lens technology for glare-free light and high energy efficiency
- 02 Ledlenser Connect App and wireless Bluetooth® remote control enable personalization and remote control of the light functions
- **03 Infinitely dimmable** via three-way switch
- 04 Powerbank function with USB connection for charging electronic devices
- **05 Red light** to maintain night vision ability
- **06** Rubber hook for hanging the light, integrated magnet for mounting it on metal surfaces, and a removable stand with a built-in metal hook that can be flipped out to provide more light mounting options
- **07** Convenient and safe charging via Magnetic Charge System
- **08** Integrated battery and charge status indicator

GLARE-FREE 360° ILLUMINATION WITH REMOTE CONTROL



— ML-SERIES







DESIGN AWARD 2019		DIE ESP		PRODUCT VIDEO		DI SE DI PRODUCT VIDEO
	• LEOLENSER	of the state of th	• LEOLENSER	Techological and the second of	• LEDLENSER	©8 Solution of the state of the

		ML4	ML4 Warm Light
	ED		
\triangle	LED Configuration	9x Power LED, 9x LED Rot	9x Power LED, 9x LED Rot
all	Light Functions	Boost / Power / Mid Power / Low Power (+ Blink, alle Light Functions auch in Rot)	Boost / Power / Mid Power / Low Power (+ Blink, alle Light Functions auch in Rot)
<u>-\̈́\</u> -	Luminous Flux¹ (lm)	300 / 150 / 50 / 5	300 / 150 / 50 / 5
□ ⇒	Beam Distance ¹ (m)	-	-
<u>(b)</u>	Run Time ¹ (h)	- / 2.5 / 8 / 45	- / 2.2 / 7 / 40
В	ATTERY AND CASE		
	Battery	1x 14500 Li-ion Battery 3.7V	1x 14500 Li-ion Battery 3.7V
<u> </u>	Battery Capacity² (Wh / mAh)	2.77 / 750	2.77 / 750
٩	Rechargeable	Yes	Yes
Ō	Charging Time⁵ (min)	150	150
ф	IP Level	IP66	IP66
S	IZE AND WEIGHT		
\bigcirc	Diameter (mm)	34.5	34.5
7	Height (mm)	97	97
ğ	Weight incl. Battery (g / oz)	71 / 2.5	71 / 2.5
T	ECHNOLOGY		
	Micro Prism Technology	•	•
	Temperature Control	•	•
P	Powerbank Function	-	
<u></u>	Magnetic Charge System	•	•
	Dual Power Source	•	•
	More Features	Low Battery Warning, Charge Indicator, Battery Indicator, Transportation Lock, Red Light	Low Battery Warning, Charge Indicator, Battery Indicator, Transportation Lock, Red Light
P	ACKAGING		
	Item no. Window Box / GTIN	502053 / 4058205017886	502231 / 4058205022125
	Content Box	1 Set of Batteries, Magnetic Charging Cable	1 Set of Batteries, Magnetic Charging Cable
0	PTIONAL ACCESSORIES		
Fu	rther accessories on page 72	502271 USB Adapter 2.4A	502271 USB Adapter 2.4A

ML <mark>6</mark>	ML6 Warm Light	ML6 Connect WL
18x Power LED, 6x LED Rot	18x Power LED, 6x LED Rot	18x Power LED, 6x LED Rot
Boost / Power / Low Power (+ Blink, Pulse, S.O.S., Strobe, all functions also in red)	Boost / Power / Low Power (+ Blink, Pulse, S.O.S., Strobe, all functions also in red)	Boost / Power / Mid Power / Low Power (+ Blink, Pulse, Position, Strobe, S.O.S., Alpine emergency signal, all functions also in red)
750 / 550 / 5	750 / 550 / 5	750 / 550 / 100 / 5
-	-	-
- / 4 / 240	- / 3.5 / 200	- / 3.5 / 12 / 180
1x 18650 Li-ion Battery 3.6V	1x 18650 Li-ion Battery 3.6V	1x 18650 Li-ion Battery 3.6V
10,89 / 3000	10.89 / 3000	10.89 / 3000
Yes	Yes	Yes
300	300	300
IP66	IP66	IP66
42	42	45
178	178	178
280 / 9.9	280 / 9.9	260 / 9.2
•	•	•
•	•	•
•	•	•
		•
Low Battery Warning, Charge Indicator, Battery Indicator, Dimmable, Transporta- tion Lock, Red Light, Memory Mode	Low Battery Warning, Charge Indicator, Battery Indicator, Dimmable, Transporta- tion Lock, Red Light, Memory Mode	Low Battery Warning, Charge Indicator, Battery Indicator, Dimmable, Transporta- tion Lock, Red Light, Bluetooth®, Memory Mode, Emergency Light
500929 / 4058205011259	502084 / 4058205017916	502201 / 4058205021203
1 Set of Batterie, Stand, Transport Bag, Micro-USB Cable	1 Set of Batterie, Stand, Transport Bag, Micro-USB Cable	1 Set of Batterie, Stand, Transport Bag, Magnetic Charging Cable

502126 Flex3 Powerbank

502126 Flex3 Powerbank

¹⁻⁹ Information on page 84

502126 Flex3 Powerbank

PORTABLE ENERGY FLEX-SERIES







FLEX-SERIES: THE FUTURE OF PORTABLE ENERGY



► FOR 21700 BATTERIES FLEX5

5 FI FX10

FOR 21700 BATTERIES	FLEXO	FLEXIU
TECHNICAL SPECS	Powerbank+	Powerbank+
✓ Length (mm)	103	120
→ Width (mm)	41	54
🕽 Height (mm)	28	29
Weight with Battery (g / oz)	126 / 4.4	235 / 8.3
Weight without Battery (g / oz)	55 / 1.9	164 / 5.8
TECHNOLOGY		
⊐ Battery	1x 21700 Li-ion Battery 3.7V	2x 21700 Li-ion Battery 3.7V
■ Battery Capacity² (Wh / mAh)	16.65 / 4500	33.30 / 9000
다 IP Level	IP65	IP65
Rechargeable	Yes	Yes
Charging Time ⁵ (min)	140	240
Energy Status	Battery Indicator, Charge Indicator, Low Battery Warning	Battery Indicator, Charge Indicator, Low Battery Warning
FEATURES	6-IN-1	6-IN-1
	Powerbank with replaceable battery	Powerbank with replaceable battery
	2. IP65 – water and dust protection	2. IP65 – water and dust protection
	Battery Charger (up to 30 % shorter charging time – compared to charging in a P7R CORE / WORK / SIGNATURE)	 Battery Charger (up to 30 % shorter charging time – compared to charging in a P7R CORE / WORK / SIGNATURE)
	4. Safe Battery Storage	4. Safe Battery Storage
	5. Double protection against short circuit (box and battery)	Double protection against short circuit (box and battery)
	6. Battery Charge Indicator	Battery Charge Indicator for both batteries
MATCHES		
	H7R Core, P7R Core, P7R Signature, P9R Core LEP	H7R Core, P7R Core, P7R Signature, P9R Core LEP
PACKAGING		
Item no. Box / GTIN	502511 / 4058205026697	502127 / 4058205019286
Content	1 Rechargeable Battery, USB Cable (USB-A to USB-C)	2 Rechargeable Batteries, USB Cable (USB-A to USB-C)















Rethinking the Powerbank: Innovative 6-in-1 System

Flexible, sustainable, powerful – that distinguishes our new Flex series; the ideal addition for all outdoor activities.

The rechargeable batteries of the new Ledlenser powerbanks can be removed at any time and are easy to swop out after being drained.

Therefore, the powerbanks can charge the 18650 respectively 21700 batteries used in compatible Ledlenser lights and in other electronic devices.





(USB Type-A to Type-C) Micro-USB cable included



1-9 Information on page 84

FLEX-SERIES: EVEN MORE POWER ON THE GO



TECHNICAL SPECS	Powerbank+	Powerbank+
Length (mm)	109	109
→ Width (mm)	27	47
Theight (mm)	27	27
Weight with Battery (g / oz)	88 / 3.1	164 / 5.8
Weight without Battery (g / oz)	40 / 1.4	116 / 4.1
TECHNOLOGY		
	1x 18650 Li-ion Battery 3.6V	2x 18650 Li-ion Batteries 3.6V
■ Battery Capacity² (Wh / mAh)	12.34 / 3400	24.68 / 6800
্ৰ IP Level	IP65	IP65
(a) Rechargeable	Yes	Yes
ि Charging Time⁵ (min)	240	240
Energy Status	Battery Indicator, Charge Indicator, Low Battery Warning	Battery Indicator, Charge Indicator, Low Battery Warning
FEATURES	6-IN-1	6-IN-1

- 1. Powerbank with replaceable battery
- 2. IP65 water and dust protection
- 3. Battery Charger (up to 30 % shorter charging time compared to charging in a P6R CORE / WORK / SIGNATURE)
- 4. Safe Battery Storage
- 5. Double protection against short circuit (box and battery)
- 6. Battery Charge Indicator

- 1. Powerbank with replaceable battery
- 2. IP65 water and dust protection
- 3. Battery Charger (up to 30 % shorter charging time – compared to charging in a P6R CORE / WORK / SIGNATURE)
- 4. Safe Battery Storage
- 5. Double protection against short circuit (box and battery)
- 6. Battery Charge Indicator for both batteries

MATCHES

► FOR 18650 BATTERIES

P6R Core, P6R Signature


P6R Core, P6R Signature

PACKAGING		
Item no. Box / GTIN	502126 / 4058205019255	502125 / 4058205019224
Contents Box	1 Rechargeable Battery, Micro-USB Cable	2 Rechargeable Batteries, Micro-USB Cable











ACCESSORIES FLASHLIGHTS

C = Core S = Signature

ARTNR.	MODELL	P2R C	P3 C	P4 C	P4R C	P5 C	P5R C	P6 C
0337	Pouch Type D	•	•			•		
502249	Lamp Adapter Type B						•	
0362	Universal Mounting System							•
501025	Remote Switch Type E							•
0380	USB Car Charger	•			•		•	
502265	Magnetic Charging Cable Type A						•	
502259	Charging Station Type A						•	
502596	Li-lon direct USB rech, Battery 3.6 V / 880 mAh						•	
500985	14500 Li-lon rechargeable battery 750 mAh					•	•	

Magnetic charging cable with

Standard USB A plug



Item no. 0342 Pouch Belt bag made of robust polyamide fabric with elastic side walls



Item no. 502256 **Universal Mounting Bracket** Stable universal fastening to cylindrical objects

ARTNR.	MODELL	P17R C	P18R \$
0042	Signal Cone 53mm Orange	•	
0380	USB Car Charger		•
502265	Magnetic Charging Cable Type A		•




Diverse Item no.

The plastic plug-in attachment quickly transforms a flashlight into a versatile red signal light at any time, e.g. for signal light









pants, can be rotated 360 rotated

Charging Station Professional charging station incl. magnetic charging cable, compatible with 5 Station Charging Pa

Item no. 502262



Item no. 0317 **Intelligent Clip** Practical belt clip for attachment to the

Item no. 0362 **Universal Mounting System**

This universal mounting fixes flashlights with a diameter of 25-34 mm securely to tripods, rods and tubes in next to no time. The light and fixation are aligned in parallel









Four high quality color filters: Red maintains night vision ability. Green and red are suitable for animal observation, among other things. Yellow improves visibility in fog. Blue improves the visibility of liquids


Item no. 502269 Leather Pouch durable leather protective bag



ACCESSORIES HEADLAMPS

C = Core S = Signature

ARTNR.	MODELL	HF4R C	HF6R C	HF8R C / HF8R C RGB	H5 C	H5R C	H7R C	H15R C	H19R C
0332	Pouch Type H	•	•	•	•	•			
502253	Belt Clip Type A							•	•
502314	Helmet Connecting Kit Type H	•	•	•	•	•	•	•	•
502313	Helmet Band Fixing Clip Type A				•	•	•	•	•
502256	Universal Mounting Bracket Type E	•	•	•	•	•	•	•	•
502451	Transparent Silicone Headband Type A				•	•	•	•	•
502469	Headband+Overheadband Core				•	•	•	•	•
502311	Bluetooth®8 Remote Control Type A			•					
502265	Magnetic Charging Cable Type A	•	•	•		•	•	•	•
502312	Extension Cable Type C							•	•
502262	21700 Li-ion Recharge. Battery 4800mAh						•		
502411	Bluetooth®8 2x 21700 Batterybox							•	•
502511	Powerbank Flex5						•		
502127	Powerbank Flex10						•		
502310	2x 21700 Li-lon Recharge. Battery Pack							•	•
502929	USB-C Adapter 20W	•	•	•					







Item no. 502314 **Helmet Connecting** Kit Type H Stable helmet holder system for a wide variety

of helmet models





Item no. 502256 **Universal Mounting Bracket** Stable universal fastening





Practical extension cable (120 cm) that is plugged in between the lamp head and the battery box - so the battery can easily be stowed in the backpack





Item no. 502265

Magnetic Charging Cable Magnetic charging cable with standard USB-A connector



ARTNR.	MODELL	ML4/WL	ML6/WL	ML6 C WL
502311	Bluetooth®® Remote Control Type A			•
02265	Magnetic Charging Cable Type A			•
02595	Li-Ion direct USB rech. Battery 3,6 V / 2500 mAh		•	•
02596	Li-Ion direct USB rech. Battery 3,6 V / 880 mAh	•		
00985	14500 Li-lon rechargeable battery 750 mAh	•		
02126	Powerbank Flex3		•	•
02125	Powerbank Flex7		•	•
00986	14500 Li-lon battery 750 mAh & external charger	•		
501001	Li-Ion rechargeable Battery 3,6 V / 3000 mAh		•	





TECHNOLOGIES, ABOUT US, WARRANTY AND MORÉ





LEDLENSER TECHNOLOGY ABC



LASER EXCITED PHOSPHOR TECHNOLOGY

Need a highly focused white light with an extreme beam range? We have you covered with the Laser Excited Phosphor Technology. This is how it works: Blue laser light is directed at a phosphor-coated plate and transformed into white light which then travels through two lenses, resulting in a white light that is highly focused and has an extreme range. You can use it for Morse code or on search and rescue missions.



ACTIVE COOLING TECHNOLOGY

High luminosity requires special measures. A powerful fan actively cools down the high-end LED and allows maximum light output over long periods of time – while remaining consistently energy-efficient.





ADAPTIVE LIGHT BEAM


Our Adaptive Light Beam technology dims and focuses automatically. This way, the light is adapted to changing environments and obstacles; from uneven forest ground and wet sidewalks to narrow machine compartments – without manual control. The system detects blinding reflections as well as overall light conditions and controls all light sources separately. This does not only result in an ideal illumination and focusing, but it also enables completely hands-free use, with an extended battery runtime.





ADVANCED FOCUS SYSTEM (AFS)


Galileo swore by the power of lenses; Newton by the power of reflectors. We have simply combined the two Technologies – only better than anyone before. The result: our patented Advanced Focus System (AFS), which allows a seamless transition from homogeneous low beam to sharply focused high beam.





COOLING TECHNOLOGY


Cooling Technology (CT) ensures your head stays cool even when your light is at maximum power. Our CT products reduce LED heat to the optimal level by means of the intelligent use of cooling elements. This technology is also used to cool computer chips and ensures highly efficient use of energy, increased illuminating power, and especially long-lasting LEDs.





DIGITAL ADVANCED FOCUS SYSTEM

Our patent-pending Digital Advanced Focus System (dAFS) allows a virtually seamless transition from homogeneous flood-light to focused spotlight. Its efficiency delights even experts. The technology enables a slim design, ideal lighting for different ranges and permanent peripheral vision.





DUAL POWER SOURCE

Our Dual Power Source allows you to use the full performance of your Ledlenser at any time – no matter what power source you have available. This technology recognizes the power source and you can therefore. You can therefore choose between the rechargeable Ledlenser battery or a disposable battery. Extremely practical for long trips without a power point.





EMERGENCY LIGHT

This feature turns your flashlight into an emergency light: If the power goes out while your Ledlenser is on the charging base, it will automatically turn on. So the light helps you find your way around, e. g. to the breaker panel.





EXTREME SEARCH BEAM

Our Extreme Search Beam consists of several powerful LEDs and a unique optical system for extreme long-range vision. The light is sharply focused to prevent glare at close range. The ultimate light beam for long-range vision.







FLEX SEALING TECHNOLOGY


The innovative Flex Sealing Technology ensures that the electronic parts of the lamp head are completely sealed off, to protect against the penetration of water and dust. This flexible system maintains the seal, even when the Advanced Focus System is used. The focus can even be used underwater.



(

RAPID FOCUS

When focusing or defocusing the flashlight or headlamp, the reflector lens moves in relation to the LED. To ensure this process is as quick and ergonomic as possible we developed Rapid Focus: a single-hand mechanism that allows the light beam to be adjusted as fast as lightning.





FLOATING CHARGE SYSTEM

Grab-and-go wireless charging. The Floating Charge System is a wall-mounted magnetic charging system, getting the light ready to go with a simple flick of the wrist. It also offers USB charging with an adapter system that can be plugged into standard outlets or car lighters.





SAFETY YTRION CELL

Ledlenser's Safety Ytrion Cell is a special lithium iron phosphate battery with unique properties: The technology combines high energy density with superior durability and safety, even in rough use and adverse storage conditions.





FUSION BEAM


By combining different LEDs and lenses, lights with Fusion Beam have a unique, application-optimized illumination. This simultaneously enables a homogenous close-up wide flood beam and sharply focused long-distance beam. The intensity of the flood and spot beams can be individually adjusted thanks to independent controls for each light source.





SMART LIGHT TECHNOLOGY (SLT)

This innovation turns a Ledlenser into your personal lighting tool:
A micro-controller allows individual ranges of functions to be programmed to different touch and switch combinations. That way, you always have the perfect light mode at hand.








MAGNETIC CHARGE SYSTEM

With the Magnetic Charge System, the charging cable can quickly and easily be attached to the light. The connection for charging the battery is made via magnetic contacts. When the contacts approach each other, the charging cable automatically pairs with the light. The connection is automatically released under load.





TEMPERATURE CONTROL

Our lights stay cool, even when they work hard. Thanks to the intelligent and fully automated temperature control, a Ledlenser never gets too hot, no matter how much it is used. This protects you from burns and the LED from overheating.





MULTI-CORE OPTICS

Multi-Core Optics harness and direct the light emitted from extremely powerful, next-generation LEDs. The special faceted lens tames and directs the light, resulting in a homogeneous beam and aesthetic illumination.





X-LENS TECHNOLOGY

This technology is an enhancement of the Advanced Focus System. It can merge virtually any number of reflector lenses and synchronizes their individual light beams into a perfect beam, resulting in a high-grade, homogeneous floodlight in unfocused mode and our most sharply focused high beam to date.







LEDLENSER

WHAT SETS US APART

- One of the global market leaders in portable lights. That includes: Flashlights, headlamps, work lights, floodlights, lanterns, EX-protected lights
- > "German Engineering & Design": In-house development, production and quality assurance
- > Inventor of the trendsetting and patented³ Advanced Focus System
- > 7-year warranty⁴ for most products in connection with online registration
- More than 100 industrial property rights as well as more than 200 awards and prizes for our products
- > More than 650 employees worldwide
- Company-owned offices in Germany, China, USA, Japan, Denmark, United Kingdom, France, Italy and Switzerland
- > Worldwide collaboration with more than 40 master distributors

To ensure that our bright ideas see the light of day, we clearly divided up our tasks: "Engineered in Germany, produced in China". Our production expertise is concentrated at our location in Yangjiang, Guangdong. Every product is manufactured and tested here; from prototype to mass production.

The checklist for quality control includes 24 tests: Endurance, extreme temperatures, water, salt, impact, pressure and more - inspected and tested until the products have overcome all obstacles and meet our quality standards. Furthermore, it is important to us to take responsibility for our employees in China. We do this for example by building company housing and through our involvement in social and intercultural projects.









When the two brothers Harald and Rainer Opolka from Solingen started out, they really didn't have much more than a garage, an old Atari computer, a set of tools, a drawing pad and around 1000 Deutschmarks of seed capital. Today, the former garage company of both the Ledlenser founders is an internationally operating company and one of the global market leaders in portable lights. The German Ledlenser brand conquered the flashlight market in the year 2000. The approach of equipping a flashlight with an LED instead of a bulb as a light source was absolutely visionary at that point in time. Millions of the "V8 Photon Pump" were sold worldwide and it constituted a new era of portable light – the "P7" achieved the same thing several years later.

To meet our objective as an LED pioneer, we are still using this technological advantage today in the development of new products – particularly in times during which LED lighting has become the norm in so many places and genuine quality is becoming harder and harder to recognize. At the same time, our premise "German Engineering & Design" has guided us from day one and justifies our unique commitment to quality. Ledlenser products give users worldwide the freedom of doing their jobs to the best of their ability or pursuing their passion with devotion – with the best possible light on their side.





LEDLENSER GUARANTEED QUALITY







TÜVRheinland

ZERTIFIZIERT

Management System ISO 9001:2015 ISO 14001:2015 ISO 50001:2018

www.tuv.com ID 9108640713

QUALITY

"German Engineering & Design" - this statement stands for the highest development and production standards in regard to technology, design, materials and workmanship. We hold more than 100 industrial property rights. These include patents, utility models and designs. We are proud of having received various design awards for our products.

WARRANTY

Since we are confident in the quality of our lights, we grant a seven-year warranty on nearly all products in connection with online registration. All original Ledlenser products covered by our warranty include a product registration card. To register, simply scan the QR code with a smartphone or enter the indicated URL on your laptop or PC.

ISO CERTIFICATION

We meet the requirements of the ISO 9001, ISO 14001 and ISO 50001 standards and are certified by $T\ddot{U}V$ Rheinland.

Quality management: DIN EN ISO 9001:2015

Our systematic quality management ensures a consistently high quality of our products and services. Clearly defined and comprehensible processes enable us to meet our customers' expectations consistently and professionally. We also meet the standard requirements at our Chinese location.

Environmental management: DIN EN ISO 14001:2015

Our company has defined an internal environmental policy and precise environmental objectives. Here, the focus is on the establishment and realization of an environmental management system, to ensure continuous improvements – e. g. in regard to CO_2 emissions, the use of resources and other environmental factors.

Energy management: DIN EN ISO 50001:2018

We operate energy management geared towards sustainability. This includes measures to reduce the consumption of energy such as electricity, gas and fuel as well as specific risk prevention.



¹⁻⁹ Information on page 84

— NOTES

The information pertaining to package contents, appearance, performance, dimensions and weight corresponds to the information available at the time of publication. In the interest of product development, we reserve the right to change package contents, appearance, design and color without prior notice. Product images may vary from the actual products and may show optional accessories which can be purchased separately. Errors and misprints excepted.

- 1) Measurements according to ANSI FL1 on the respective setting. If no setting is explicitly indicated, the values refer to luminous flux (Lumen/lm) and beam distance (meters/m) on the highest setting and to the run time (hours/h) on the lowest setting. If the light is equipped with color LED(s), the measurements indicated apply to white light or white LED. A boost function (if applicable) can be used several times, but only for short periods of time. If the light has different energy modes, measurement is based on "energy saving mode."
- 2) Calculated capacity value in watt-hours (Wh) or milliampere hours (mAh). This applies to the delivery state of the battery/ies inside the respective item, or for lights with rechargeable battery/ ies, to the rechargeable battery/ies inside the product when fully
- 3) EP Patent 1880139: US Patent 7.461.960

4) Two year warranty from the date of purchase, or seven years with online registration through our website. The warranty applies worldwide; legal warranty rights also apply. It covers defects in material and manufacture. Battery packs are guaranteed to work correctly for 24 months. This warranty does not cover products in the "Solidline" series, the LiteWallet®, the Powercase, the Batterybox7, the Kidled-Series also the Ledlenser K-Serie (except K3),, as well as defective batteries, holsters, pouches, remote switches, color filters, imprints and surface coatings. The warrantor is Ledlenser GmbH & Co. KG, Kronenstr. 5-7, 42699 Solingen, Germany. For more information visit ledlenser. com/warranty

- 5) The average charging time of the batteries in the delivery state in minutes may vary depending on the power supply unit used.
- 6) Additional talk time using the example of an iPhone X when charging with the fully charged batteries contained in the content of the article in question.
- 7) EP Patent 3376097
- 8) The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of these by Ledlenser GmbH & Co. KG is under license
- 9) EP Patent 3717826

You can find our terms and conditions at www.ledlenser.com

Ledlenser GmbH & Co. KG Kronenstraße 5-7, 42699 Solingen, Germany Sales tax ID: DE815242425, Local Court Wuppertal, HRA 23078 Personally liable partner: Ledlenser Beteiligungs GmbH Headquarters: Solingen, Germany Local Court Wuppertal, HRB 24774 Executive Director: Michael Reuter (CEO), Kai Milewski (CFO)

-LEDLENSER WE'RE LOOKING FORWARD TO HEARING FROM YOU

We are always looking for ways to improve our support for you and your customers. We greatly appreciate any feedback you have on how we can build the Ledlenser brand together.

CONTACT SALES GERMANY vertrieb@ledlenser.com

CONTACT TECHNICAL SUPPORT

For uncomplicated and fast processing, please contact our Consumer Care Team for all services, product, warranty and goodwill questions.

Customers from Germany can reach us by e-mail: support@ledlenser.com

Customers from Belgium, the Netherlands and Luxembourg can reach us by e-mail: info.bnl@ledlenser.com

Customers from Austria can reach us by e-mail: support@ledlenser.at

Customers from Switzerland can reach us by e-mail: office@ledlenser.ch











